

CS1774

4-Port USB VGA/Audio KVME™ Switch with Ethernet Hub



CS1774 is a multi-computer KVM Switch with built-in 3-in-1 (KVM Switch, USB 2.0 and Ethernet) function. It can simultaneously control 4 servers via a set of USB keyboard, mouse, and monitor. Moreover, the built-in USB and Ethernet Switch ports can rapidly access USB peripheral devices and share Internet resources at ease.

Features

- USB 2.0 KVME™ Switch with Ethernet Hub/USB Hub
- Five auto-sensing dual speed ports (Ethernet/Fast Ethernet) plugand-and-play enabled; hub complies with IEEE802.3/IEEE802.3u Standard
- 2 port USB 2.0 Hub built in
- Multiplatform support: compatible with all operation platforms PC(Windows,Linux and most others), Mac and Sun
- With speaker and microphone support
- Bi-directional switching and flexible interoperability:switch permits independent PC, independent peripheral, and independent audio function, regardless of KVM switch focus
- · Buzzer On/Off via hotkey
- · Keyboard and mouse emulation for error free booting
- · Computer selection via front panel pushbuttons and hotkeys
- superior video quality up to 2048 x 1536; DDC2B
- OŚ Compatibility:Windows 98, Windows ME, Windows 2000, Windows 2003, Windows XP, Windows Vista, LINUX, Mac OS 8.6/9/10 and SUN Solaris 8/9.
- SUN/Mac keyboard support and emulation*
 - *1.PC keyboard combinations emulate SUN/Mac keyboards.
 - *2.SUN/Mac keyboards only work with their own computers.

Specification


Computer Connections	4
Port Selection	Hotkey, Pushbutton
USB Port / Audio Port Selection	Hotkey
Connectors	
Console Ports	2 x USB Type A Female (White) 1 x HDB-15 Female (Blue) 1 x Mini Stereo Jack Female (Green) 1 x Mini Stereo Jack Female (Pink)



KVM Ports	4 x SPHD-15 Female (Green) 4 x Mini Stereo Jack Female (Green) 4 x Mini Stereo Jack Female (Pink)	
USB Hub	2 x USB Type A Female (White)	
Firmware Upgrade	1 x RJ-11 Female (Black)	
Power	1 x DC Jack(Black)	
Switches		
Ports	4 x Pushbutton	
LEDs		
USB Link	4 (Green)	
10/100 Mbps	5 (Green)	
On Line /Selected	4 (Orange)	
Link	5 (Green)	
Emulation		
Keyboard / Mouse	USB	
Video	2048 x 1536; DDC2B	
Scan Interval	1-99 seconds	
Power Consumption	DC 5.3V, 5W	
Environmental		
Operating Temperature	0-50°C	
Storage Temperature	-20°-60°C	
Humidity	0-80% RH, Non-condensing	
Physical Properties		
Housing	Metal	
Weight	0.92 kg (2.03 lb)	
Dimensions (L x W x H)	27.00 x 8.80 x 5.55 cm (10.63 x 3.46 x 2.19 in.)	
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.	



Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.