
CS62U

2-Port USB VGA/Audio Cable KVM Switch (1.8m)



CS62U 2-Port USB KVM Switch has a handy design integrating with 1.8m of cables. It can control 2 servers via a single console.



Features

- One USB console controls two USB computers
- Compact design, built-in 1.8 m cables
- Hotkey selection for OS and keyboard language
- [Computer Selection via hotkey and USB mouse](#) **NEW!**
- Multiplatform support - Windows, Linux, Mac, Sun
- [Video DynaSync™](#) - exclusive ATEN technology eliminates boot-up display problems and optimizes resolution when switching between ports
- [Console mouse port emulation/bypass feature supports most mouse driver](#) **NEW!**
- [USB mouse port can be used for USB hub and USB peripheral sharing](#) *
- [Supports gaming keyboards](#) **NEW!**
- [Supports multifunction and wireless keyboards and mice](#) **NEW!**
- All-in-one design
- With speaker support
- Superior video quality – up to 2048 x 1536; DDC2B
- Auto Scan function to monitor computer operation
- Non-powered
- Sun/Mac keyboard support and emulation*

* 1. PC keyboard combinations emulate Sun/Mac keyboards

2. Sun/Mac keyboards only work with their own computers

Specifications

2-Port USB KVM Switch

Computer Connections	2
Port Selection	Hotkey, Mouse
Connectors	
Console Ports	2 x USB Type A Female (White) 1 x HDB-15 Female (Blue) 1 x Mini Stereo Jack Female (Green)
KVM Ports	2 x USB Type A Male (Black) 2 x HDB-15 Male (Blue) 2 x Mini Stereo Plug Male (Green)
LEDs	
Selected	2 (Green)
Cable Length	
Computer	1.8 m (6 ft)
Emulation	
Keyboard / Mouse	USB
Video	2048 x 1536, DDC2B
Scan Interval	5 seconds
Environmental	
Operating Temperature	0 - 50°C
Storage Temperature	-20 - 60°C
Humidity	0-80% RH, Non-condensing
Physical Properties	
Housing	Plastic
Weight	0.37 kg (0.81 lb)
Dimensions (L x W x H)	8.75 x 6.08 x 2.80 cm (3.44 x 2.39 x 1.1 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Topology Diagram

