

CS1942

2-Port USB Mini DisplayPort/Audio Dual Display KVM™ Switch (Cables included)



The CS1942 2-port USB 2.0 Dual View Mini DisplayPort [KVM™](#) Switch allows access to 2 computers from a single USB keyboard and USB mouse with dual displays. The KVM switches amazing functionality combines a Dual view 2-port Mini DisplayPort switch, with a 2-port USB 2.0 hub, and front panel USB quick charge port for mobile devices.

The CS1942 further improves on previous KVM designs with the latest Mini-DisplayPort and Mini-TOSLINK connectors. It also provides the capability of digital video & audio with reliable Ultra high resolution, vivid picture quality, surround sound with SPDIF connections.

The CS1942 is ideal for multimedia applications, and offers the ultimate in [space-saving](#), streamlined KVM technology for the desktop.

Features

- One dual-view USB console independently and simultaneously controls two Mini DisplayPort computers and two USB devices
- [USB quick charge mode \(front panel USB port\)](#)
- [Mini DisplayPort 1.1a & HDCP compatible](#)
- [Full bass response provides a rich experience for digital surround sound systems via Mini-TOSLINK](#)
- [Superior video quality – enables up to 2560 x 1600 resolution and 3D displays up to 1920x1080 resolution at 120Hz](#)
- [Nvidia 3D Vision Ready](#)
- 2-port USB 2.0 hub built in, fully compliant with USB 2.0 specifications
- Computer selection via front touch panel /hotkeys/ mouse*
- Independent switching for USB peripherals, audio, and KVM focus
- Keyboard and Mouse support emulation and bypass
- Power on Detection
- Mac keyboard support and emulation**
- Multilingual keyboard mapping – Supports English, Japanese, and French keyboards
- Multiplatform support – Windows, Linux and Mac

* Mouse port switching is only workable under mouse emulation mode. For 3-key USB wheel mouse only.

**PC keyboard combinations emulate Mac keyboards.

**Mac keyboards only work with their own computers.

Specifications

Computer Connections	2
Port Selection	Touch Panel, Hotkey, Mouse
Connectors	

Console Ports	2 x USB Type A Female (Black, rear panel) 2 x Mini DisplayPort Female (Black) 2 x Mini TOSLINK Jack Female (Black) 1 x 3.5mm Audio Jack Female (Green) 1 x 3.5mm Audio Jack Female (Pink)
KVM Ports	2 x USB Type B Female (White) 4 x Mini DisplayPort Female (Black) 2 x Mini TOSLINK Jack Female (Black)
USB Hub	2 x USB Type A Female (White; 1 x Front panel, 1 x Rear panel)
Power	1 x DC Jack
Switches	
Selected	3 x Point Touch Panel
LEDs	
KVM	2 (Orange)
Audio	2 (Green)
USB	2 (Green)
Emulation	
Keyboard / Mouse	USB
Video	DP: 2560 x 1600 resolution @ 60Hz, or 3D Display 1920 x 1080 resolution @ 120Hz
Scan Interval	1 – 99 seconds (Default: 5 seconds)
Power Consumption	DC5.3V:2.33W:45BTU
Environmental	
Operating Temperature	0 – 50°C
Storage Temperature	–20 – 60°C
Humidity	0 - 80% RH, Non-condensing
Physical Properties	
Housing	Plastic
Weight	0.56 kg (1.23 lb)
Dimensions (L x W x H)	19.70 x 19.70 x 4.47 cm (7.76 x 7.76 x 1.76 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their
 respective owners.