

## CS1792

2-Port USB HDMI/Audio KVMP™ Switch



With the unique design and innovative features, the CS1792 USB 2.0 HDMI KVMP™ Switch provides both style and functionality for today's multimedia SOHO environment.

Combining a 2-port switch with a 2-port USB 2.0 hub, the CS1792 provides seamless HDMI signal switching between 2 PCs or other HDMI-enabled devices, such as gaming consoles, and allows users to share USB peripherals from a single console. The CS1792 provides enhanced independent switching via front panel pushbuttons and keyboard hotkeys, and features Video DynaSync™ technology to ensure that HDMI display resolution is always optimized. With integrated digital audio, the CS1792 also allows users to experience high-definition sound, such as Dolby True HD and DTS HD Master Audio.

Ideal for multimedia applications in the office, the CS1792 offers the ultimate in space-saving, streamlined KVM technology for the desktop.



### Features


- 2-port HDMI USB 2.0 KVMP™ Switch
- One USB console controls two HDMI-interface computers and two additional USB devices
- 2-port USB 2.0 hub built in; fully compliant with the USB 2.0 specification
- Independent switching of KVM, USB peripheral, and audio focus via front panel pushbuttons and hotkeys
- HDMI digital monitor support - fully compliant with HDMI; also HDCP compliant
- Dolby True HD and DTS HD Master Audio support
- Superior video quality - supports 480i, 480p, 720p, 1080i, and 1080p(HDTV)/1920 x 1200(DVI)
- Power on detection - If one of the computers is powered off, the CS1792 will automatically switch to the next powered-on computer
- Supports widescreen resolutions
- Multiplatform support - Windows, Linux, and Mac
- Console mouse port emulation/bypass feature supports most mouse driver and multifunction mice
- Video DynaSync™ - stores the console monitor's EDID (Extended Display Identification Data) to optimize display resolution
- Complete keyboard emulation for error-free booting
- Mac keyboard support and emulation\*
- Auto Scan Mode for monitoring all computers and HDMI devices
- Firmware Upgradable

\* 1. PC keyboard combinations emulate Mac Keyboards  
2. Mac keyboards only work with their own computers

# Specification

Computer Connections	2
Port Selection	Hotkey, Pushbutton
Connectors	
Console Ports	2 x USB Type A Female (rear panel) 1 x HDMI Female (Black) 2 x 3.5 mm Audio Jack Female (Green; 1 x front, 1 x rear) 2 x 3.5 mm Audio Jack Female (Pink; 1 x front, 1 x rear)
KVM Ports	2 x USB Type B Female 2 x HDMI Female (Black) 2 x 3.5 mm Audio Jack Female (Green) 2 x 3.5 mm Audio Jack Female (Pink)
Firmware Upgrade	1 x 3.5 mm Audio Jack Female (Black)
Power	1 x DC Jack
USB Hub	2 x USB Type A Female (1 x front panel; 1 x rear panel)
Switches	
Selected	3 x Pushbutton
LEDs	
Audio	3 (Green)
KVM	3 (Orange)
USB	3 (Green)
Emulation	
Keyboard / Mouse	USB
Video	1920 x 1080 @ 60Hz / 1920 x 1200 @ 60Hz
Scan Interval	1-99 seconds (default: 5 sec.)
Power Consumption	DC5.3V:2.7W:28BTU
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20-60°C
Humidity	0-80% RH, Non-condensing
Physical Properties	
Housing	Metal, Plastic
Weight	0.42 kg ( 0.93 lb )
Dimensions (L x W x H)	20.63 x 7.24 x 4.40 cm (8.12 x 2.85 x 1.73 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.