

## VE300RQ

VGA/Audio Cat 5 Receiver with Auto Deskew (1280 x 1024@300m)



The VE300RQ A/V Over CAT5 Extender system is designed to integrate seamlessly into installations with the ATEN [VM0808T](#) CAT5 A/V Matrix Switch or stand alone using the [VE300T](#) and the VE300RQ. With ATEN's exclusive Deskew technology, the [VE300](#) allows you to extend the distance between the A/V source and the display monitor by up to 500 feet (150 m) with a resolution of 1600x1200 (for the [VE300R](#)), or up to 1000 feet (300 m) with a resolution of 1280x1024 (for the VE300RQ).

It is able to accomplish this by means of a local transmitting unit (the [VE300T](#)), connected to the remote receiving unit (either the [VE300R](#) or VE300RQ), using Cat 5e twisted pair cable. Because it allows access to the audio/video source over large distances, the [VE300](#) is ideal for installations such as construction sites, factory floors, control and security centers, where the system equipment can reside in a safe and secure location, while the display is conveniently located in public view.

### Features

- Uses Cat 5e cable to connect the Transmitter and Receiver
- Extends A/V source in [VM0808T](#) installations
- Supports one local and one remote displays
- Superior RGB deskew function (VE300RQ)– automatically synchronizes the time delay of RGB signals to compensate for distance
- Long Distance Transmission up to 1000 feet (300 m)
- Superior video quality
- [VE300R](#): 1920x1200@60Hz 100 feet (30 m), 1600x1200@60Hz 500 feet (150 m ), 1280x1024@60Hz 650 feet (200 m)
- Automatic and adjustable gain control – adjust signal strength to compensate for distance
- Supports wide screen
- Rack-mountable
- Built-in 8KV/15KV ESD protection

## Specification

Video Output	
Interfaces	1 x HDB-15 Female (Blue)
Impedance	75 $\Omega$
Video	
Max. Bandwidth	300 MHz
Max. Resolutions / Distance	1920 x 1200@150m; 1280 x 1024@300m
Audio Outputs	
Interfaces	Stereo: 1 x Mini Stereo Jack Female (Green)
Connectors	
Power	1 x DC Jack (Black)
Power Consumption	DC5.3V:3.7W:17BTU
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20 - 60°C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Metal
Weight	0.47 kg ( 1.04 lb )
Dimensions (L x W x H)	20.20 x 8.20 x 2.50 cm (7.95 x 3.23 x 0.98 in.)
Carton Lot	5 pcs
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

## Diagram



### ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.