

VS881

8-Port VGA Switch with Auto Switching



The VS881 is a video switch with 8 ports. It allows 8 independent computers or notebook computers to display their video outputs on a single monitor or on the screen via a multimedia projector. It provides a best solution of presentations and speeches to enterprises and education centers.

- Displays the video output of eight separate computers on a single monitor or projector
- Modern concentric design with intuitive connector layout for quick and easy access
- Fast and convenient computer selection via pushbuttons or infrared (IR) remote control
- Extra-thin infrared handset allows easy storage in the mother unit
- · Electronic switching for greater reliability and durability
- Easy installation no software required no confi guration
- Superior video quality up to 2048x1536; DDC; DDC2; DDC2B
 Supports VGA, SVGA, XGA,UXGA, QXGA and multisync monitors

Specification

Video Input	
Interfaces	8 x HDB-15 Male (Blue)
Impedance	75 Ω
Max. Distance	1.8 m
Video Output	
Interfaces	1 x HDB-15 Female (Blue)
Impedance	75 Ω
Max. Distance	10 m
Video	
Max. Bandwidth	300 MHz
Max. Resolution	Up to 1920 x 1440



Max. Distance	Up to 10 m	
Control		
IR	1 x Mini Stereo Jack Female (Black)	
Connectors		
Power	1 x DC Jack	
Power Consumption	DC5V:1.22W:6BTU/h	
	Note: The measurement in Watts indicates the typical power consumption of the device with no external loading. The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.	
Environmental		
Operating Temperature	0 - 50°C	
Storage Temperature	-20 - 60°C	
Humidity	0 - 80% RH, Non-Condensing	
Physical Properties		
Housing	Plastic	
Weight	0.45 kg (0.99 lb)	
Dimensions (L x W x H)	17.35 x 19.13 x 4.50 cm (6.83 x 7.53 x 1.77 in.)	
Carton Lot	5 pcs	
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.	



Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.