

## 2L-2403

3M VGA Cable



The VGA Cable is designed to provide a high quality VGA connection, ideally suited for high resolution applications up to 1920 x 1200. This durably constructed VGA video cable eliminates the picture ghosting and fuzzy images, guaranteeing users the ultimate A/V experiences.



### Features

- Optimized for analog signal transmission
  - VGA cable with 15-pin female input and male output
  - Bend Radius: 90°\*
  - Outer shielded material: Al Mylar tape
  - RoHS compliant
  - Compatible with ATEN VGA products
- Note:\* Swings 1000 times between angles of +/- 90 degrees, at a frequency of 30 times per minute

**Specifications**

Conductor	
Material	Tinned Copper
Conductor Diameter	30 AWG
Jacketed	
Material	Jacket: PVC Shielding: AL-Mylar
Connectors	
Video	HDB-15 Male HDB-15 Female
Cable Length	3 m

**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their respective owners.