

## US4322

2 x 2 USB 3.2 Gen 1 Sharing Switch



essentials

# 2 X 2 USB 3.2 Gen 1 Sharing Switch



US4322

SuperSpeed

# 5 Gbps

Data Transfer

## Computer



USB-A x2

## Peripheral



USB-A x2



### Bus-Powered Design

## Multiplatform Support

Windows | macOS | Linux



Accent Light



One-Button Switch

Style Meets Efficiency. One-Touch USB Sharing.



**essentials** 2 X 2 USB 3.2 Gen 1 Sharing Switch **US4322**

All references to and depictions of compatible products, including those produced by Apple or Elgato, are for compatibility/administration purposes only, not intended to suggest any endorsement or sponsorship by or affiliation with those product manufacturers.

The US4322 is a compact 2-Port USB Sharing Switch that enables users to effortlessly share data between two computers. It's highly portable and ideal for professional and personal workspaces. With an intuitive push-button operation and a space-efficient design, the US4322 is a valuable addition to any dual-computer desktop setup - whether you're working, creating, or working hard. For more information, please visit our website at [www.aten.com](http://www.aten.com) or contact your local distributor.



Aesthetic

Compact.

Portable.





Share All Devices with One-Button Switch





Save Time with 5 Gbps  
SuperSpeed Data Transfer







## What's in the Box



2 X 2 USB 3.2 Gen 1 Sharing Switch

US4322



USB Type-A to Type-A cable x2  
(1.5 m)

### Talk to Our Experts

If you prefer to have ATEN contact you, please complete the form and a representative will be in touch with you shortly

First Name \*

Last Name \*

- Country \*

Company \*

Email \*

Phone Number \*

- Customer Type \*

Job Title \*



**Features**

- InstaSync™ Technology
  - Fast USB switching capability that keeps the flow smooth and uninterrupted
  
- Two USB Device Sharing Across Two Computers
  - Farewell to the need of swapping cables and peripherals between two separate computers
  
- 5 Gbps Data Transfer with USB 3.2 Gen 1
  - Up to 5 Gbps SuperSpeed data transfer rates, which is about 10 times faster than the USB 2.0 standard, allow users to transfer large files quickly and efficiently
  
- Quick Switch via Built-In Pushbutton
  - Enjoy the hassle-free experience of switching USB peripherals between two systems with just one single button press
  
- Compact Enclosure with Accent Lighting
  - Aesthetically pleasing with its accent lighting and a casing so compact that it occupies very little space
  
- Hot Pluggable
  - Allows adding / removal of the peripherals/computers connected to the installation without having to power down the switch. Besides, no drivers or software is required
  
- OS Independent
  - Compatible with mainstream operating systems including Windows, macOS, and Linux

**Specifications**

|                        |                                                                                                                                 |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Computer Connections   | 2                                                                                                                               |
| Port Selection         | Pushbutton                                                                                                                      |
| Connectors             |                                                                                                                                 |
| Computer               | 2 x USB Type-A Female (Blue)                                                                                                    |
| Device                 | 2 x USB Type-A Female (Blue)                                                                                                    |
| Cable Length           |                                                                                                                                 |
| USB Cable              | 2 x USB 3.2 Gen 1 Type-A to Type-A Cable (1.5 m)                                                                                |
| LEDs                   |                                                                                                                                 |
| Selected               | 2 (Orange)                                                                                                                      |
| Power                  | 2 (Orange, Bottom Side)                                                                                                         |
| Environmental          |                                                                                                                                 |
| Operating Temperature  | 0 – 40 °C                                                                                                                       |
| Storage Temperature    | -20 – 60 °C                                                                                                                     |
| Humidity               | 10 – 80 % RH, Non-condensing                                                                                                    |
| Physical Properties    |                                                                                                                                 |
| Housing                | Plastic                                                                                                                         |
| Weight                 | 0.03 kg ( 0.07 lb )                                                                                                             |
| Dimensions (L x W x H) | 6.10 x 5.65 x 1.52 cm<br>(2.4 x 2.22 x 0.6 in.)                                                                                 |
| Carton Lot             | 20 pcs                                                                                                                          |
| Note                   | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |


Diagram

Lap




US

**US4322  
Rear View**



**US4322  
Front View**



US



or

Can

Printer



Simply Better Connections

**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.