

CS1794

4-Port USB HDMI/Audio KVMP™ Switch



With its unique design and innovative features, the CubiQ™ CS1794 USB 2.0 HDMI KVMP™ Switch provides both style and functionality for today's multimedia SOHO environment. Combining a 4-port switch with a 2-port USB 2.0 hub, the CS1794 provides seamless HDMI signal switching between 4 PCs or other HDMI-enabled devices, such as gaming consoles, and allows users to share USB peripherals from a single console.

The CS1794 provides enhanced independent switching via front panel pushbuttons and keyboard hotkeys, and features Video DynaSync™ technology to ensure that HDMI display resolution is always optimized. With integrated digital audio, the CS1794 also allows users to experience high-definition sound, such as Dolby True HD and DTS HD Master Audio.

Ideal for multimedia applications in the office, the CubiQ™ CS1794 offers the ultimate in space-saving, streamlined KVM technology for the desktop.



Features

- 4-port HDMI USB 2.0 KVMP™ Switch
- One USB console controls four HDMI-interface computers and two additional USB devices
- 2-port USB 2.0 hub built in; fully compliant with the USB 2.0 specification
- Independent switching of KVM, USB peripheral, and audio focus via front panel pushbuttons and hotkeys
- HDMI digital monitor support - fully compliant with HDMI; also HDCP compliant
- Dolby True HD and DTS HD Master Audio support
- Superior video quality - supports 480i, 480p, 720p, 1080i, and 1080p(HDTV)/1920 x 1200(DVI)
- Power on detection - If one of the computers is powered off, the CS1794 will automatically switch to the next powered-on computer
- Supports widescreen resolutions
- Multiplatform support - Windows, Linux, and Mac
- Console mouse port emulation/bypass feature supports most mouse driver and multifunction mice
- Video DynaSync™ - stores the console monitor's EDID (Extended Display Identification Data) to optimize display resolution
- Complete keyboard emulation for error-free booting
- Mac keyboard support and emulation*
- Auto Scan Mode for monitoring all computers and HDMI devices
- Firmware Upgradable

* 1. PC keyboard combinations emulate Mac Keyboards

2. Mac keyboards only work with their own computers

Specifications

| | |
|--|--|
| | |
|--|--|

| | |
|-----------------------|--|
| Computer Connections | 4 |
| Port Selection | Hotkey, Pushbutton |
| Connectors | |
| Console Ports | 2 x USB Type A Female (rear panel) 1 x HDMI Female (Black) 2 x 3.5 mm Audio Jack Female (Green; 1 x front, 1 x rear) 2 x 3.5 mm Audio Jack Female (Pink; 1 x front, 1 x rear) |
| KVM Ports | 4 x USB Type B Female 4 x HDMI Female (Black) 4 x 3.5 mm Audio Jack Female (Green) 4 x 3.5 mm Audio Jack Female (Pink) |
| Firmware Upgrade | 1 x 3.5 mm Audio Jack Female (Black) |
| Power | 1 x DC Jack |
| USB Hub | 2 x USB Type A Female (1 x front panel; 1 x rear panel) |
| Switches | |
| Selected | 5 x Pushbutton |
| LEDs | |
| Audio | 5 (Green) |
| KVM | 5 (Orange) |
| USB | 5 (Green) |
| Emulation | |
| Keyboard / Mouse | USB |
| Video | 1920 x 1080 @ 60Hz / 1920 x 1200 @ 60Hz |
| Scan Interval | 1-99 seconds (default: 5 sec.) |
| Power Consumption | DC5.3V:3.62W:43BTU |
| Environmental | |
| Operating Temperature | 0-50°C |
| Storage Temperature | -20-60°C |
| Humidity | 0-80% RH, Non-condensing |
| Physical Properties | |
| Housing | Metal, Plastic |
| Weight | 0.53 kg (1.17 lb) |

| | |
|------------------------|---|
| Dimensions (L x W x H) | 26.23 x 7.68 x 4.40 cm (10.33 x 3.02 x 1.73 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.