
KA7520

PS/2 VGA KVM Adapter



The KA7520 PS/2 KVM Adapter Cable connects the KVM switch to the video, PS/2 mouse and PS/2 keyboard ports of the target computer. With its small form factor and light weight design, it fits perfectly into most of the rack-mount or desktop servers.

Note: The video quality of KA7520 has been enhanced to Full HD. To distinguish between the FHD and non-FHD versions, please refer to below link: [FHD & Non-FHD Comparison](#)

Features

- Keyboard and mouse emulation - keeps your server functioning smoothly when it is disconnected from the switch's KVM port or relocated to different KVM port
- Lifetime firmware upgrades
- Superior video quality - supports resolution up to 1920 x 1200 (Reduced blanking)*
- Hot pluggable - add or remove computers without having to power down the switch.
- Compact size

* This maximum resolution may vary depending on the transmission distance. For more details, please refer to the product pages of the connected KVM switches.

Specifications

Connectors	
Link	1 x RJ-45 Female
Computer	2 x 6-pin Mini-DIN Male 1 x HDB-15 Male
LEDs	
Online	1 (Green)
Power	1 (Orange)
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20–60°C
Physical Properties	
Housing	Plastic
Weight	0.14 kg (0.31 lb)
Dimensions (L x W x H)	9.00 x 4.30 x 2.18 cm (3.54 x 1.69 x 0.86 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram

