

KA9140

Serial KVM Adapter



The Altusen serial CPU adapters connect KVM cables to the serial ports of the servers. Those adapters are light and in small form factor, fit perfectly into most of the rack-mount or desktop servers.


Features

- Auto Signal Compensation (ASC), no DIP switch setting needed for the different distances.
- Hot pluggable - add or remove computers without having to power down the switch.
- Support VT-100.
- Lifetime firmware upgrades.
- Built in ASIC for greater reliability and compatibility.
- CPU module designed with automatic conversion to allow for flexible interface combinations (PS/2, USB) to control all computer types (Serial).

Specifications

Connectors	
Console Ports	1 x RJ-45 Female 1 x Min Din Female 1 x HDB-15 Female 1 x Earphone-Jack-4 Female
Computer	1 x DB-9 Female
LEDs	
Power	1 (Orange)
Link	1 (Green)
Switches	1 x 2 way slide switch
Power Consumption	DC5V:1.60W:10BTU/h Note: <ul style="list-style-type: none"> ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20-60°C
Humidity	0-80% RH, NC
Physical Properties	
Housing	Metal
Weight	0.50 kg (1.1 lb)
Dimensions (L x W x H)	20.00 x 8.15 x 2.50 cm (7.87 x 3.21 x 0.98 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their
 respective owners.