
VS0202

2x2 VGA/Audio Matrix Switch



The VS0202 Video Matrix Switch allows video and audio from 2 computers to be routed to 2 monitors, projectors and speakers. Ideal for presentations and applications where information from multiple computers is being delivered to multiple destinations.

Features

- Each of the 2 video outs can toggle between Source 1 and Source 2 using front panel pushbuttons.
- Audio enabled
- Duplicate and enhance video signals to up to 30 m (max.) *
- Expandable: Cascade to ATEN's video splitters to support hundreds of video displays
- With up to 200 MHz Video Bandwidth
- OS Support: Windows 2000, Windows XP, Linux, Mac and Sun

* Video content sent over very long distance using a VGA cable might result in slight degradation of the video signal and quality

Specifications

Video Input	
Interfaces	2 x HDB-15 Male (Blue)
Impedance	75 Ω
Max. Distance	1.8 m
Video Output	
Interfaces	2 x HDB-15 Female (Blue)
Impedance	75 Ω
Video	
Max. Bandwidth	200 MHz
Max. Resolution	Up to 1920 x 1200
Max. Distance	Up to 30 m
Audio	
Input	2 x Mini Stereo Jack Female (Green)
Output	2 x Mini Stereo Jack Female (Green)
Connectors	
Power	1 x DC Jack
Power Consumption	DC5.3V:2.43W:11BTU
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20 - 60°C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Metal
Weight	0.47 kg (1.04 lb)
Dimensions (L x W x H)	13.00 x 7.61 x 4.40 cm (5.12 x 3 x 1.73 in.)
Carton Lot	20 pcs
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram

