

VS92A

2-Port VGA Splitter (350MHz)



The VS92A is a video splitter that not only duplicates the video signal from any VGA, XGA, SVGA, UXGA, or multisync monitor to two outputs, but also boosts the video signal over a distance of up to 30 meters. Cascadable to support up to 8 displays, and offering bandwidth up to 350 MHz, the VS92A is ideal for broadcasting and enhancing video information to the public, monitoring your work environments from safe locations, or offering superior video for company or classroom training.

Features


- One video input to 2 video outputs
- Cascadable to 3 levels - provides up to 8 video signals
- Supports 350 MHz bandwidth
- Long-distance transmission - up to 30 m *
- Superior video quality - 1920 x 1440@60Hz
- DDC, DDC2, DDC2B Compatible (Port 1 only)
- Supports VGA, XGA, SVGA, UXGA, WUXGA and multisync monitors
- All metal casing

* Video content sent over very long distance using a VGA cable might result in slight degradation of the video signal and quality.

Specifications

| | |
|------------------------|---|
| Video Input | |
| Interfaces | 1 x HDB-15 Male (Blue) |
| Impedance | 75 Ω |
| Max. Distance | 1.8 m |
| Video Output | |
| Interfaces | 2 x HDB-15 Female (Blue) |
| Impedance | 75 Ω |
| Video | |
| Max. Bandwidth | 350 MHz |
| Max. Resolution | Up to 1920 x 1440 |
| Max. Distance | Up to 30 m |
| Connectors | |
| Power | 1 x DC Jack |
| Power Consumption | DC9V:1.15W:5BTU/h Note: <ul style="list-style-type: none"> ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded. |
| Environmental | |
| Operating Temperature | 0-50°C |
| Storage Temperature | -20 - 60°C |
| Humidity | 0 - 80% RH, Non-Condensing |
| Physical Properties | |
| Housing | Metal |
| Weight | 0.42 kg (0.93 lb) |
| Dimensions (L x W x H) | 13.00 x 7.51 x 4.40 cm (5.12 x 2.96 x 1.73 in.) |
| Carton Lot | 20 pcs |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.