

## AS251S

RS232 Serial Auto Switch (2 to 1)



AS251S allows 2 PCs to share 1 serial (RS232) printer. It is easy to install and needs no additional power supply.

### Features

- No External Power required.
- Output Port Selectable.
- Transparent to the user.
- OS Compatibility: WIN98, WIN ME, WIN 2K and WIN XP.

## Specifications

|                        |                                                                                                                                                                                                                                                                                                             |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connectors             |                                                                                                                                                                                                                                                                                                             |
| Input                  | 2 x RS-232 DB-25 Female                                                                                                                                                                                                                                                                                     |
| Output                 | 1 x RS-232 DB-25 Male                                                                                                                                                                                                                                                                                       |
| LEDs                   |                                                                                                                                                                                                                                                                                                             |
| Input                  | 2                                                                                                                                                                                                                                                                                                           |
| Port Selection         | Auto / Manual                                                                                                                                                                                                                                                                                               |
| Input Arbitration      | First come first served                                                                                                                                                                                                                                                                                     |
| Function Key           | Manual / Select                                                                                                                                                                                                                                                                                             |
| Cable Length           | 15 m [50'] (max.)                                                                                                                                                                                                                                                                                           |
| Timeout Selection      | 10 ~ 60 seconds                                                                                                                                                                                                                                                                                             |
| Power Consumption      | AC9V:0.1W:0.46BTU/h<br><br>Note:<br><ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul> |
| Environmental          |                                                                                                                                                                                                                                                                                                             |
| Operating Temperature  | 0 ~50°C                                                                                                                                                                                                                                                                                                     |
| Storage Temperature    | -20 ~ 60°C                                                                                                                                                                                                                                                                                                  |
| Humidity               | 0~80% RH, NC                                                                                                                                                                                                                                                                                                |
| Physical Properties    |                                                                                                                                                                                                                                                                                                             |
| Housing                | Plastic                                                                                                                                                                                                                                                                                                     |
| Weight                 | 0.05 kg ( 0.11 lb )                                                                                                                                                                                                                                                                                         |
| Dimensions (L x W x H) | 9.30 x 7.70 x 2.55 cm<br>(3.66 x 3.03 x 1 in.)                                                                                                                                                                                                                                                              |
| Note                   | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.                                                                                                                                                                             |

### ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their respective owners.