

US3344

4 x 4 USB 3.2 Gen1 Peripheral Sharing Switch



ATEN US3344 is a 4-port USB 3.2 Gen1 peripheral sharing device that allows users to share four USB devices between 4 different general computers by using USB 3.2 Gen 1 Type-B to Type-A cables.

The US3344 allows for a neat and tidy installation –The connecting cables are bundled to save the extra cost of purchasing USB cables. The additional USB 3.2 Gen 1 Type-B to Type-C cable included in the US3344 package, which can connect to the USB-C computers and allows for hybrid and flexible usage, is the most cost-effective solution for USB-C equipped laptops and tablet computers

The US3344 is USB 3.2 Gen1 compliant, which can support data transfer rate up to 5Gbps and backwards compatible with USB 2.0 and USB1.1. It is perfect for high-bandwidth devices, such as USB docking stations or HD cameras.

In addition, the US3344 also features an external remote port selector that can simplify desktop layout, and select which computer needs to use the USB devices. With its compact and all-in-one design, you can create a space saving, convenient and productive work environment.


Features

- Enables 4 computers to share 4 USB 3.2 Gen1 devices
- Simple port selection via remote port selector for convenient switch placement
- USB 3.2 Gen1 compliant, supporting data transfer rates of up to 5Gbps
- LEDs indicates which computer is active
- Over-current protection
- Micro USB power jack for additional power supply
- Bus-powered – no external power supply needed
- Plug and Play – no drivers or external power adapter needed
- Multiplatform support – Windows, Linux and Mac

Specifications

Computer Connections	4
Port Selection	Remote port selector
Connectors	
Computer	4 x USB Type B Female (Blue)
Device	4 x USB Type A Female (Blue)
Power (Optional)	1 x USB micro B Female (Black)
Cable Length	
USB Cable	USB 3.1 Gen 1 B to A Cable 1.2m x 2 USB 3.1 Gen 1 B to A Cable 1.8m x 2 USB 3.1 Gen 1 B to C Cable 1.8m x 2
Remote Port Selector	1.8 m
LEDs	
Selected	4 (White)
Environmental	
Operating Temperature	0–40°C
Storage Temperature	-20–60°C
Humidity	0–80% RH, Non-condensing
Physical Properties	
Housing	Plastic
Weight	0.13 kg (0.29 lb)
Dimensions (L x W x H)	9.37 x 9.30 x 2.68 cm (3.69 x 3.66 x 1.06 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.