

## UC100KMA

PS/2 to USB Adapter with Mac support (30cm)




UC100KMA is a signal converter with a 30cm cable. It can convert signals of PS/2 devices (keyboard and mouse) into USB signals, and supports multiple operating systems to fulfill the needs of users.

### Features

- Two PS/2 devices (keyboard and mouse) to USB Interface converter
- Supports PS/2 mice and microsoft IntelliMouse
- Hotkey selection for OS and keyboard language supports
- Compatible with KVM Switches
- USB specification compliant
- External power adapter not required
- Easy installation - no software required
- OS Support: Windows 2000, Windows XP, [Windows Vista](#), LINUX, Mac, Sun and FreeBSD

## Specifications

|                        |                                                                                                                                                                                                                                                                                                            |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connectors             |                                                                                                                                                                                                                                                                                                            |
| USB Port               | 1 x USB Type A Male (White)                                                                                                                                                                                                                                                                                |
| PS/2 Keyboard          | 1 x 6-pin Mini-DIN Female (Purple)                                                                                                                                                                                                                                                                         |
| PS/2 Mouse             | 1 x 6-pin Mini-DIN Female (Green)                                                                                                                                                                                                                                                                          |
| LEDs                   |                                                                                                                                                                                                                                                                                                            |
| Link                   | 2 (Green)                                                                                                                                                                                                                                                                                                  |
| Cable Length           | 30 cm                                                                                                                                                                                                                                                                                                      |
| Platforms              | Windows 2000/XP/Vista/Linux<br>Mac OS 8.6 or Higher SUN Solaris 8                                                                                                                                                                                                                                          |
| Data Rate              | 12 Mbps                                                                                                                                                                                                                                                                                                    |
| Power Mode             | Bus Powered (via the USB cable)                                                                                                                                                                                                                                                                            |
| Power Consumption      | DC5V:0.374W:6BTU/h<br><br>Note:<br><ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul> |
| Environmental          |                                                                                                                                                                                                                                                                                                            |
| Operating Temperature  | 0–50°C                                                                                                                                                                                                                                                                                                     |
| Storage Temperature    | -20–60°C                                                                                                                                                                                                                                                                                                   |
| Humidity               | 0–80% RH, Non-condensing                                                                                                                                                                                                                                                                                   |
| Physical Properties    |                                                                                                                                                                                                                                                                                                            |
| Housing                | Plastic                                                                                                                                                                                                                                                                                                    |
| Weight                 | 0.08 kg ( 0.18 lb )                                                                                                                                                                                                                                                                                        |
| Dimensions (L x W x H) | 9.15 x 4.70 x 2.50 cm<br>(3.6 x 1.85 x 0.98 in.)                                                                                                                                                                                                                                                           |
| Note                   | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.                                                                                                                                                                            |

**Diagram****ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.