



Nightclub Uses ATEN Media Matrix Solution to Enhance Audiovisual Effects and Multimedia Entertainment



Overview

Multiple displays for broadcasting music videos and commercials were installed in a popular nightclub. The various content needs to be flexibly delivered to monitors located in the stage and bar areas.

ATEN Solution

VM0808T 8x8 Cat 5 A/V Matrix Switch



- Connects any of 8 Cat 5 A/V inputs to any of 8 Cat 5 A/V outputs in combination with ATEN VE500 A/V Over Cat 5 Extender system
- Supports Video Quality up to 1920 x 1200@60Hz; DDC2B
- Easily switch between multiple sources and multiple displays
- Supports additional local input and local display

VE500 A/V Over Cat 5 Transmitter / Receiver




- Long Distance Transmission up to 300 m
- Uses Cat 5e cable to connect the Transmitter and Receiver
- Superior video quality 1920x1200 @60Hz (30 m); 1600x1200 @60Hz (150 m)

Benefits

- Different vivid multimedia content can be delivered to monitors located around the nightclub
- High quality A/V signals can be seamlessly delivered over long distance
- Update the latest entertainment videos to the monitors with ease and flexibility
- Efficiently assist nightclub staff to check the A/V signals from source devices locally

Solution Setup





Features





VM0808T


8x8 Cat 5 A/V Matrix Switch

- Supports additional local input and local display provides an extra input output source
- Flexible configuration and control
 - Local Operation: Front panel LCD display and pushbuttons + Serial controller
 - Remote Operation: Browser-based Graphical User Interface (GUI) + Telnet
- Serial RS-232 support
- Independent switching of audio and video sources any audio source can be connected to any video source for output flexibility
- Automatic and adjustable video and audio quality

Front View



Rear View



VE500

A/V Over Cat 5 Extender with RS-232, Balanced Audio



- Superior audio quality balanced audio provides flawless long-distance transmission
- Automatic and adjustable gain control adjust signal strength to compensate for distance
- Provides RS-232 channel

VE500T | Transmitter





Rear View Audio Out Port Video Out Port Balanced Audio Out Port Unit to Unit Port

ATEN International Co., Ltd

E-mail: marketing@aten.com