

VS82

Wandplatte (Kunststoff) für 2-Port-VGA-Splitter (250 MHz)



The VS82 Video Splitter duplicates the video signal from an input source (i.e. a computer) and route it to up to 2 display devices (monitors, projectors, etc.). However, they go beyond being merely duplicators, in that they also enhance the video signals over distances up to 30 meters. Furthermore, they can be cascaded three levels to additional ATEN video splitters to support many numerous display devices. And they mount inconspicuously on the wall or out of sight.

Funktionen und Merkmale

- One video input to 2 video outputs.
- Cascadable to 3 levels - provides up to 8 video signals.
- Supports up to 250 MHz bandwidth.
- Long distance transmission - up to 30 m (210'). *
- High video resolution - up to 1920 x 1440.
- DDC, DDC2, DDC2B Compatible (Port 1 only).
- Compact design with convenient topside connection, lays flat on a desktop or mounts on the wall.
- Supports VGA, XGA, SVGA, UXGA and multisync monitors.
- OS Support: Windows 2000, Windows XP, Linux, Mac and Sun

* Bildinhalte, die lange Übertragungswege über ein VGA-Kabel zurücklegen, können Pegel- und Qualitätsverluste erleiden.

Specification

Videoeingang	
Schnittstellen	1 x HDB-15-Stecker (Blau)
Max. Entfernung	1,8 m
Impedanz	75 Ω
Videoausgang	
Schnittstellen	2 x HDB-15-Buchse (Blau)
Impedanz	75 Ω
Video	
Max. Bandbreite	250 MHz
Max. Auflösungen	Bis 1920 x 1440
Max. Entfernung	Bis 30 m
Anschlüsse	
Stromversorgung	1 x Gleichspannungsanschluss
Stromverbrauch	DC9V:1.02W:5BTU/h Hinweis: ● Die Messung in Watt gibt die typische Leistungsaufnahme des Geräts ohne externe Belastung an. ● Die Messung in BTU/h gibt die Leistungsaufnahme des Geräts an, wenn es voll belastet ist.
Umgebung	
Betriebstemperatur	0-50°C
Aufbewahrungstemperatur	-20 - 60°C
Feuchtigkeit	0 – 80 % relative Luftfeuchte, nicht kondensierend
Physikalische Eigenschaften	
Gehäuse	Kunststoff
Gewicht	0.14 kg (0.31 lb)
Abmessungen (L x B x H)	8.76 x 11.46 x 3.33 cm (3.45 x 4.51 x 1.31 in.)
Kartonposten	20 Stk.
Hinweis	Bei einigen Rack-Mount Produkten ist zu beachten, dass die üblichen Abmessungen von BxTxH in einem LxBxH-Format angegeben werden.

Diagramm



ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their
 respective owners.