

CS102U

2-Port USB VGA KVMP™ Switch



CS102U is a KVM Switch with built-in USB. It can control 2 servers via a single console and allows servers to share 2 peripheral devices via the USB ports on the rear panel. Users can switch between computers via the buttons on the front panel the switch. It is the simplest and most convenient solution for multi-computer management.

Features

- One USB console controls 2 computers
- 2 port USB Hub built in
- Control a Mac and a PC at the same time
- Computer selection via front panel pushbuttons
- Superior video quality up to 1920 x 1440; DDC2B
- Supports Microsoft IntelliMouse and the scrolling wheel on most mice
- Auto Scan function to monitor computer operation
- Non-powered
- OS Support:Windows 2000, Windows XP, <u>Windows Vista</u>, LINUX, Mac and FreeBSD



Specification

| Computer Connections | 2 |
|---------------------------|--|
| Port Selection | Pushbutton |
| Connectors | |
| Console Ports | 2 x USB Type A Female (White) 1 x HDB-15 Female (Blue) |
| KVM Ports | 2 x USB TYPE B Female (White) 2 x HDB-15 Male (Blue) |
| USB Hub | 2 x USB Type A Female (White) |
| Power | 1 x DC Jack (Black) |
| LEDs | |
| Online | N/A |
| Selected | 2 |
| Auto Scan | N/A |
| Video | 1920 x 1440; DDC2B |
| Scan Interval | 5 seconds |
| Power Consumption | DC5V:0.11W:26BTU/h |
| | Note: • The measurement in Watts indicates the typical power consumption of the device with no external loading. • The measurement in BTU/h indicates the power consumption of the device when it is fully loaded. |
| Environmental | |
| Operating Temperature | 0~50°C |
| Storage Temperature | -20~60°C |
| Humidity | 0~80% RH, Non-condensing |
| Physical Properties | |
| Housing | Plastic / Metal |
| Weight | 0.15 kg (0.33 lb) |
| Dimensions (L x W x H) | 12.00 x 6.52 x 4.40 cm (4.72 x 2.57 x 1.73 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |
| | |



Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd. ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd. All rights reserved. All other trademarks are the property of their respective owners.