

## CS74E

4-Port PS/2 VGA Slim KVM Switch



The KVM (Keyboard, Video, Mouse) switch is a control unit that allows access to four computers from a single console (keyboard, monitor, and mouse). With its custom designed connectors, the significantly reduces the number of ports required for a 4 port KVM switch. The design features a custom SPHD-15 male connector for the keyboard, video, and mouse, and SPHD-15 female connectors for the cables that connect the switch to the computers.

### Features

- One PS/2 console controls 4 computers.
- Compact, modern case for convenient attractive placement.
- Custom connector layout.
- Power on detection - automatically switches to the first powered on port.
- Computer selection via front panel pushbuttons and hotkeys.
- Superior video quality - up to 2048 x 1536; DDC2B.
- Supports Microsoft IntelliMouse and the scrolling wheel on most mice.
- Auto Scan function to monitor computer operation.
- Bus-Powered.
- ATEN ASIC inside.
- OS Support: Windows 2000, Windows XP, [Windows Vista](#), LINUX and FreeBSD

**Specification**

|                        |   |
|------------------------|---|
| Computer Connections   | 4   |
| Port Selection         | Hotkey, Pushbutton  |
| Connectors             |   |
| Console Ports          | 1 x SPHD-15 Male (Yellow)   |
| KVM Ports              | 4 x SPHD-15 Female (Yellow)   |
| Power                  | 1 x DC Jack   |
| Switches               |   |
| Ports                  | 4 x Pushbutton  |
| LEDs                   |   |
| Selected               | 4 (Green)   |
| Emulation              |   |
| Keyboard / Mouse       | PS/2  |
| Video                  | 2048 x 1536 @ 60Hz; DDC2B   |
| Scan Interval          | 5 seconds   |
| Power Consumption      | DC5V:0.39W:6BTU/h<br><br>Note:<br><ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul> |
| Environmental          |   |
| Operating Temperature  | 0-50°C  |
| Storage Temperature    | -20-60°C  |
| Humidity               | 0~80% RH, Non-condensing  |
| Physical Properties    |   |
| Housing                | Metal   |
| Weight                 | 0.49 kg ( 1.08 lb )   |
| Dimensions (L x W x H) | 20.00 x 8.15 x 2.50 cm<br>(7.87 x 3.21 x 0.98 in.)  |
| Note                   | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.   |

Diagram



**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.