

BC48V9AH

Internal Battery Pack for OL2000LV / OL2000HV



The ATEN UPS Internal Battery Pack comes with a hot-swap design, allowing uninterrupted operations during battery replacement to ATEN UPS systems. It ensures stable power supply and offers easy installation, bringing users hassle-free management to their power equipment.

Note: When the battery pack is not in use, please recharge it for 4 ~ 6 hours every 3 ~ 6 months.



Specification

| Electrical | |
|--------------------------------------|---|
| Nominal Output Voltage | 48V |
| Battery | |
| Battery Type | Sealed Lead-Acid |
| Battery Size | 9AH |
| Battery Quantity | 4 |
| Physical Properties | |
| Dimensions (L x W x H) | 32.50 x 20.40 x 6.66 cm (12.8 x 8.03 x 2.62 in.) |
| Weight | 10.80 kg (23.79 lb) |
| Color | Black |
| Environmental | |
| Temperature (Operating / Storage) | Operating: 32 – 104 °F (0 – 40 °C) Storage: -15 – 45 °C |
| Humidity (Operating & Storage) | 0–95% |
| Elevation (Operating / Storage) | Operating: 0-10,000ft (0-3,000meter) Storage: 0-50,000ft (0-15,000meter) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd. ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd. All rights reserved. All other trademarks are the property of their respective owners.