

PE8208

20A/16A 8-Outlet 1U Outlet-Metered & Switched eco PDU





*8 outlets

*20A (UL derated 16A) / 16A

*Outlet Power Measurement

The PE8208 eoe DPU is intelligent PDUs that contains 8 AC outlets and is available in various IEC or NEMA socket configurations. It provides secure, centralized, intelligent, power management (power on, off, cycle) of data center IT equipment (servers, storage systems, KVM switches, network devices, serial data devices, etc.), as well as the ability to monitor the center's health environment via sensors*.

eco PDU supports any 3rd party v3 SNMP Manager Software and eco DC (Energy Management Web GUI). eco DC provides you with an easy method for managing multiple devices, offering an intuitive and user friendly Graphical User Interface that allows you to configure a PDU device and monitor power status of the equipment connected to it. With eco DC, the Sensor-enabled eco PDU also offers comprehensive power analysis reports which can separate by departments and locations, providing precise measurements of current, voltage, power and watt-hour in a real-time display.

With its advanced security features and ease of operation, the eco PDU is the most convenient, most reliable, and most cost effective way to remotely manage power access for multiple computer installations and allocate power resources in the most efficient way possible

Note: Sensors are optional accessories. A sensor-enabled installation is required to generate a more complete energy-efficient data and chart. Higher sensor installation density is helpful to generate more accurate data.



Features

Power Distribution

- Space saving 1U rack mount design with rear mounting
 IEC or NEMA outlet models
 3 digit 7-segment front panel LED shows Current / IP Address
 Remote users can monitor outlet status via web pages on their browsers
- Separate power for the unit's own power and its power outlets. The user interface is still accessible even when an overload condition trips the devices' circuit breaker.

Remote Access

- Remote power control via TCP/IP and a built in 10/100 Ethernet port
 Network Interfaces: TCP/IP, UDP, HTTP, HTTPS, SSL, SMTP, DHCP, NTP, DNS, 10Base-T/100Base-TX, auto sense, Ping, Telnet
 eco PDU Power Management software eco DC
 Supports SNMP Manager V3

• Operation

- Remote power outlet control (On, Off, Power Cycle) by individual outlets
 Power-on sequencing users can set the power on sequence and delay time for each port to allow equipment to be turned on in the proper order
 Easy setup and operation via a browser-based user interface
 Multibrowser support (IE, Firefox, Chrome, Safari)
 RTC support to keep the timer running during times of no power.
 Supports up to 8 user and 1 administrator accounts
 Proactive Overload Protection (POP) automatically powers off outlets when current overloads to protect operating devices

Management

- Power status measurement at the PDU or Outlet level
 LED indicators for current and IP address at Outlet level
- d-based UI for monitoring at the outlet level

- Real-time current, voltage, and kWH displayed in a browsed-based UI for monitoring at the outlet level
 Current and voltage threshold setting
 Naming support for outlets
 User outlet access assignment on an outlet-by-outlet basis.
 Event logging and syslog support
 Upgradeable firmware
 Multilanguage support: English, German, Traditional Chinese, Simplified Chinese, Japanese, French, Spanish, Italian

Security

- Two-level password security
 Strong security features include password protection and advanced encryption technologies 128 bit SSL
 Remote authentication support: RADIUS

• eco DC Energy Management Software

- Automatic discovery of all PE devices within the same intranet
- Remote real-time power measurement and monitoring
 Remote real-time power outlet management
- Remote real-time environment sensor monitoring
 Plotting/Monitoring of all PE devices
 Exceed threshold alert through SMTP and Syslog
 Power Analysis Report
- Features available only on firmware-upgraded models with -ATB part number
 - Supports SMPTS, IPv6, Modbus (Over TCP/IP), Auto Ping, TLS1.2, SSH

 - Supports IEEE 802.1X
 Authentication: LDAP, TACACS+
 UI heartbeat, schedule control, mail control, and setting rule



Specification

Function	PE8208A	PE8208B	PE8208G	PE8208Z
Electrical				
Nominal Input Voltage	100 – 120 VAC	100 – 240 VAC	100 – 240 VAC	100 – 240 VAC
Maximum Input Current	20A Max; 16A(UL de-rated)	20A Max; 16A(UL de-rated)	16A Max	16A Max (For Australia : 15A)
Input Frequency	50-60 Hz	50-60 Hz	50-60 Hz	50-60 Hz
Input Connection	NEMA 5-20P	NEMA 6-20P	IEC 60320 C20	IEC 60320 C20
Input Power	2400 VA(Max); 1920 VA(UL de-rated)	4160 VA(Max); 3328 VA(UL de-rated)	3680 VA(Max)	3680VA(Max)
Outlet Type	Total : 8 x NEMA 5-20R	Total : 7 x IEC320 C13 + 1 x IEC320 C19	Total: 7 x IEC320 C13 + 1 x IEC320 C19	Total : 7 x GB1002 10A+ 1 x GB1002 16A
Nominal Output Voltage	100 – 120 VAC	100 – 240 VAC	100 – 240 VAC	100 – 240 VAC
Maximum Output Current (Outlet)	NEMA 5-20R: 20A(Max); 16A(UL de-rated)	C13: 15A(Max); 12A(UL de-rated) C19: 20A(Max); 16A(UL de-rated)	C13: 10A(Max) C19: 16A(Max)	GB1002 : 16A(Max), GB1002 : 10A(Max)
Maximum Output Current (Bank)	20A(Max); 16A(UL de-rated)	20A(Max); 16A(UL de-rated)	16A(Max)	16A (Max)
Maximum Output Current (Total)	20A(Max); 16A(UL de-rated)	20A(Max); 16A(UL de-rated)	16A(Max)	16A (Max)
Breakers	1 x 20A Non-Fuse Breaker	1 x 20A Non-Fuse Breaker	1 x 16A Non-Fuse Breaker	1 x 16A Non-Fuse breaker
Metering	Outlet level Current, Voltage, VA , PF and KWh Monitoring	Outlet level Current, Voltage, VA , PF and KWh Monitoring	Outlet level Current, Voltage, VA , PF and KWh Monitoring	Outlet level Current, Voltage, VA , PF and KWh Monitoring
Outlet Switching	Yes	Yes	Yes	Yes
Environment Sensor Ports	2	2	2	2
Metering Accuracy	Voltage Range: 100VAC ~ 250VAC +/-1% Power Range: 100W ~ Maximum Capacity +/- 2% Current Range: 0.1A~1A +/- 0.1A, 1A~20A +/- 1%	Voltage Range: 100VAC ~ 250VAC +/-1% Power Range: 100W ~ Maximum Capacity +/- 2% Current Range: 0.1A~1A +/- 0.1A, 1A~20A +/- 1%	Voltage Range: 100VAC ~ 250VAC +/-1% Power Range: 100W ~ Maximum Capacity +/- 2% Current Range: 0.1A~1A +/- 0.1A, 1A~20A +/- 1%	Voltage Range: 100VAC ~ 250VAC +/-1% Power Range: 100W ~ Maximum Capacity +/- 2% Current Range: 0.1A~1A +/- 0.1A, 1A~20A +/- 1%
Physical Properties				
Dimensions (L x W x H)	43.24 x 22.04 x 4.40 cm (17.02 x 8.68 x 1.73 in.)	43.24 x 22.04 x 4.40 cm (17.02 x 8.68 x 1.73 in.)	43.24 x 22.04 x 4.40 cm (17.02 x 8.68 x 1.73 in.)	43.24 x 22.04 x 4.40 cm (17.02 x 8.68 x 1.73 in.)
Weight	2.84 kg (6.26 lb)			
Power Cord Length	3 m	3 m	3 m	3 m
Environmental				
Temperature (Operating / Storage)	0 – 50°C / -20 – 60°C			
Humidity (Operating & Storage)	0 – 80% RH, Non-Condensing			
Compliance				
EMC Verification	FCC, Others by Request	FCC, Others by Request	CE, Others by Request	CE, Others by Request
Safety Verification	UL, Others by Request	UL, Others by Request	CE-LVD, GOST, Others by Request	CE-LVD, Others by Request
	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.			

Diagram









