

AF241

ParaHub



AF241 is a FIFO data switch using the 2 to 1 operation mode (i.e. 2 PCs to 1 printer) and allows users to transfer files to other PCs without additional cable connections.

Features

- Shares peripherals between computers.
- Transfers files between computers.
- Supports IEEE-1284 nibble mode.
- Print job management is first come, first serve.
- Selects ports by button and software code operation.
- Non-Powered operation.
- HP Laser Jet, Canon, Epson and NEC Compatible.
- OS Support: Windows 2000, Windows XP

Specification

| | |
|------------------------|--|
| Connectors | 3 x DB-25 Female |
| LEDs | |
| Printer Activity | 2 (Red) |
| Port Selection | |
| Input | Auto / Manual PC Selection |
| Output | N/A |
| Input Arbitration | First Come First Served |
| File Transfer | Yes |
| Broadcast | No |
| Timeout Selection | 15, 45 Seconds |
| Power Consumption | DC 9V, 0.9W (Max.) Note: <ul style="list-style-type: none"> ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded. |
| Signal Range | 6 m (Max) |
| Environmental | |
| Operating Temperature | 0 ~50°C |
| Storage Temperature | -20 ~ 60°C |
| Humidity | 0~80% RH, Non-condensing |
| Physical Properties | |
| Housing | Plastic |
| Weight | 0.11 kg (0.24 lb) |
| Dimensions (L x W x H) | 9.30 x 7.70 x 2.55 cm (3.66 x 3.03 x 1 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their
respective owners.