

CS533

Tap (USB to Bluetooth KM Switch)



The CS533 is a control unit that allows access to one computer and two Bluetooth devices from one USB keyboard and mouse.

The CS533 converts normal USB keyboard and mouse input into Bluetooth signals. That way, it allows easy sharing of keyboard and mouse between your computer and Bluetooth HID devices*. CS533 provides a convenient solution to use your desktop keyboard on your Smartphone or Tablet*.

- Use a USB keyboard and mouse on two Bluetooth HID compatible devices and a PC
- Switch between PC and Bluetooth devices via hotkeys
- Supports wired/wireless multimedia keyboard and mouse
- Supports PC and Mac iOS Bluetooth media key mapping
- Adjustable device cradle for easy smartphone/tablet placement
- USB powered

* Compatibility depends on the HID profile support from smartphone/tablet



Features

- Links use of a USB keyboard and mouse* between a PC and 2 Bluetooth devices
- Quick switch access to the computer and Bluetooth devices via hotkey
- Supports PC and Mac iOS Bluetooth media key mapping
- Supports wireless and multifunction keyboards
- Mac keyboard support and emulation**
- USB Keyboard/Mouse pass-thru supports: Windows 2000/XP /Vista /7, Mac and Linux
- Bluetooth signals supports: Windows 2000/XP /Vista /7, Mac OS X and iOS
- USB powered
- Firmware upgradable
- No software required

*Mouse will not function with iOS and some Bluetooth devices.

**PC keyboard combinations emulate Mac keyboards.

**Mac keyboards only work with their own computers.

Specification

PC / Bluetooth Connections	1/2
Port Selection	Hotkey
Connectors	
Keyboard	1 x USB Type A Female (White)
Mouse	1 x USB Type A Female (White)
Power	1 x USB Type A Male (White)
Cable Length	
Computer	1.8 m
LEDs	
Bluetooth Selected	2 (Blue)
Emulation	USB Bluetooth V2.1, Class 2
Environmental	
Operating Temperature	0 - 50°C
Storage Temperature	-20 - 60°C
Humidity	0- 80% RH, Non-condensing
Physical Properties	
Housing	Plastic
Weight	0.12 kg (0.26 lb)
Dimensions (L x W x H)	9.20 x 7.80 x 2.46 cm (3.62 x 3.07 x 0.97 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.