

RS22U80

RS Series Standing Network Rack



ATEN Racks are designed for mounting standard 19" rackmount equipment – servers, routers, UPS systems, switches, audio/video devices – regardless of brand. All racks provide straightforward equipment organization, excellent security and simple cable management while enabling optimum airflow. To simplify deployment, ATEN Racks comes with casters and leveling feet. The casters allow ATEN Racks to be easily maneuvered into the desired location, where it can then be secured in place by adjusting the leveling feet. The RS Series Rack contains a locking, reversible, removable front door that is perforated to promote efficient airflow, as well as locking, removable solid side panels. Locking doors and side panels prevent unauthorized access to installed equipment. The RS Series Rack provides standard features for a more cost-effective rack solution.

Features

- **High Ventilation Hexagonal Perforation**
 - Hexagonal perforated front and back doors provide higher tensile strength than round holes while ensuring efficient airflow and optimized ventilation

- **More Space for Cable Management**
 - Vertical cable management rail design in 800mm wide rack provides more space for network cable management

- **High Loading Capacity**
 - Static loading capacity up to 800KG

Specification

Physical Properties	
Rack Height (U Spaces)	22U
Type	Rack Enclosure
Package Contents	"Build-Up(Default)

	Knock-Down(Special Requirement) "
Mounting Hole Type	Square
Color	Black
Unit Dimensions(H*W*D)	1166 x 600 x 800
Maximum Device Height	1166
Maximum Device Width	600
Maximum Device Depth	800
Max/Min/Default Mounting	690/200/500
Maximum Mounting	690
Minimum Mounting	200
Default Mounting	500
Shipping Dimensions : Build-Up (H x W x D)	620 x 820 x 1180
Shipping Dimensions : Knock-Down (H x W x D)	Package1 : 1100 x 620 x 320 Package2 : 620 x 620 x 130
Shipping Weight	80
Unit weight	60
Weight capacity stationary	800
Weight capacity dynamic	600
Material	SPCC Cold Rolled Steel
Air permeability	0.65
Certifications	
Approvals	CE
Certifications	RoHS
Protection class	IP20
Shipping	
Build-Up packing Unit volume (CBM)	0.60
Knock-Down packing Unit volume (CBM)	Package1 : 0.22 Package2 : 0.05
Build-up package (20GP)	25
Build-up package (40GP)	50
Build-up package (40HQ)	100
Knock-Down package (20GP)	95

Knock-Down package (40GP)	200
Knock-Down package (40HQ)	230

ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their
respective owners.