

## CS74E

4-Port PS/2 VGA Slim KVM Switch



The KVM (Keyboard, Video, Mouse) switch is a control unit that allows access to four computers from a single console (keyboard, monitor, and mouse). With its custom designed connectors, the significantly reduces the number of ports required for a 4 port KVM switch. The design features a custom SPHD-15 male connector for the keyboard, video, and mouse, and SPHD-15 female connectors for the cables that connect the switch to the computers.

### Features

- One PS/2 console controls 4 computers.
- Compact, modern case for convenient attractive placement.
- Custom connector layout.
- Power on detection - automatically switches to the first powered on port.
- Computer selection via front panel pushbuttons and hotkeys.
- Superior video quality - up to 2048 x 1536; DDC2B.
- Supports Microsoft IntelliMouse and the scrolling wheel on most mice.
- Auto Scan function to monitor computer operation.
- Bus-Powered.
- ATEN ASIC inside.
- OS Support: Windows 2000, Windows XP, [Windows Vista](#), LINUX and FreeBSD

## Specification

Computer Connections	4
Port Selection	Hotkey, Pushbutton
Connectors	
Console Ports	1 x SPHD-15 Male (Yellow)
KVM Ports	4 x SPHD-15 Female (Yellow)
Power	1 x DC Jack
Switches	
Ports	4 x Pushbutton
LEDs	
Selected	4 (Green)
Emulation	
Keyboard / Mouse	PS/2
Video	2048 x 1536 @ 60Hz; DDC2B
Scan Interval	5 seconds
Power Consumption	DC5V:0.39W:6BTU/h  Note: <ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul>
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20-60°C
Humidity	0~80% RH, Non-condensing
Physical Properties	
Housing	Metal
Weight	0.49 kg ( 1.08 lb )
Dimensions (L x W x H)	20.00 x 8.15 x 2.50 cm (7.87 x 3.21 x 0.98 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

## Diagram



### **ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their  
 respective owners.