

CS84A

4-Port PS/2 VGA KVM Switch



CS84A is a KVM Switch with built-in PS/2 on each of the front and rear panels. It can control 4 servers via a single console and allows users to switch between computers via the buttons on the front panel of the switch or the hotkey configuration on the keyboard. It is the simplest and most convenient most convenient solution for multi-computer management.

Features


- One PS/2 console controls 4 computers.
- Computer selection via front panel pushbuttons and hotkeys.
- Superior video quality- up to 1920 x 1440; DDC2B.
- Supports Microsoft IntelliMouse, Logitech MouseMan, FirstMouse and IBM Scrollpoint Mouse.
- Compact, Sturdy, Durable Metal Housing.
- Keyboard and mouse emulation for error free booting.
- Auto Scan function to monitor computer operation.
- Bus-Powered.
- OS Support: Windows 2000, Windows XP, [Windows Vista](#), LINUX, Mac and FreeBSD

Specification

| | |
|----------------------|---|
| Computer Connections | 4 |
| Port Selection | Hotkey, Pushbutton |
| Connectors | |
| Console Ports | 1 x HDB-15 Female (Blue) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) |
| KVM Ports | 4 x HDB-15 Male (Blue) 4 x 6-pin Mini-DIN Female (Purple) 4 x 6-pin Mini-DIN Female (Green) |
| Power | 1 x DC Jack |
| Switches | |
| Ports | 4 x Pushbutton |

| | |
|------------------------|---|
| LEDs | |
| Online | 4 (Orange) |
| Selected | 4 (Green) |
| Emulation | |
| Keyboard / Mouse | PS/2 |
| Video | 1920 x 1440 @ 60Hz; DDC2B |
| Scan Interval | 5 seconds |
| Power Consumption | DC9V:0.3W:6BTU/h Note: <ul style="list-style-type: none"> ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded. |
| Environmental | |
| Operating Temperature | 0°~50°C |
| Storage Temperature | -20°~60°C |
| Humidity | 0~80% RH, Non-condensing |
| Physical Properties | |
| Housing | Metal |
| Weight | 0.78 kg (1.72 lb) |
| Dimensions (L x W x H) | 21.00 x 8.80 x 5.55 cm (8.27 x 3.46 x 2.19 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their
 respective owners.