
CS128A

8-Port PS/2 VGA KVM Switch



CS128A is a KVM Switch with 8 built-in ports. It can control 8 computers via the console. Moreover, it allows connections of up to 512 servers in 3 tiers by cascade for central control.

Features

- Microsoft Intellimouse, Logitech Firstmouse, MouseMan+...support PS/2 mice and MS mouse emulation.
- Easy PC selection via hotkeys, front panel push buttons and footswitch.
- Auto scan mode for monitoring PCs.
- Cascadable to three levels.
- One PS/2 style keyboard controls all PCs.
- Multiplatform support: DOS, Windows 2003/2000//XP/98/ME/NT and Linux.
- For more information about KVMs which can connect to CS128A, see [Compatible KVM Table](#).

Specification

| | |
|------------------------|--|
| Computer Connections | |
| Direct | 8 |
| Maximum | 512 |
| Port Selection | Pushbutton, Hotkey |
| Connectors | |
| Console Ports | 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x HDB-15 Female (Blue) |
| Computer | 8 x DB-25 Female (Black) |
| LEDs | |
| Online | 8 |
| Selected | 8 |
| Emulation | |
| Keyboard | PS/2; PC/AT |
| Mouse | PS/2; Serial |
| Video Resolution | 1920 x 1440 (Max.); DDC2AB |
| Scan Interval | 3, 5, 10, 15, 20, 30, 40, 60 Seconds |
| Power Consumption | DC 9V, 1.08W Note: ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded. |
| Physical Properties | |
| Housing | Plastic / Metal |
| Weight | 2.85 kg |
| Dimensions (L x W x H) | 36.6 x 25 x 4.5 cm |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram

