

## KA7171AK

USB-PS/2 KVM Adapter Module with Local Console and Access Control Box Kit



The KA7171AK USB-PS/2 KVM Adapter Module with Local Console and Access Control Box Kit is designed provide a full console connection locally in a KVM over IP Switch or Matrix KVM installation. The KA7171AK comes bundled with ATEN [2XRT-0015G](#) KVM over IP Access Control Box. By installing the [2XRT-0015G](#) with the KA7171AK, users can quickly and effortlessly enable or disable remote over IP control privilege from the KVM over IP switch by simply pressing the control button on the KVM over IP Access Control Box-making operation only permitted to the user at the local console. The KA7171AK allows a PS/2 or USB server to be connected to the switch via Cat 5e/6 cable and provides an extra console via USB keyboard, USB mouse, and monitor to use for extended local operations. In addition, the KA7171AK also features Privileged Console Control function prevents remote users from operating the device when a local administrator requires full control of the server— reducing conflicts and unwanted operations.

### Features

- Compatible with ATEN [2XRT-0015G](#) KVM over IP Access Control Box to grant users at the local console full control of access to servers
- Cat 5e/6 cable connects the device and KVM switch
- Supports computers with PS/2 or USB keyboards and mice
- Local console operation - control your system from the extended USB keyboard, USB mouse, and monitor via local console
- Pushbutton operating mode selection for privileged console control
- Built-in ASIC for greater reliability and compatibility
- USB overcurrent detection and prevention
- Built-in ESD protection and surge protection
- Superior video quality - supports resolution up to 1920 x 1200 (Reduced blanking)\*
- Supports VGA , SVGA , SXGA , UXGA , WUXGA and multisyncmonitors; local monitor supports DDC; DDC2; DDC2B
- Easy to install – no software required - connecting cables to the devices is all it takes


\* This maximum resolution may vary depending on the transmission distance. For more details, please refer to the product pages of the connected KVM switches.

### Specification

Connectors	
Console Ports	2 x USB Type A Female (White) 1 x HDB-15 Female (Blue)
KVM Ports	1 x SPHD-18 Female (Yellow)
Power	1 x DC Jack (Black)
USB Port	1 x USB Type A Female (White)

Control	1 x PS/2 1 x RJ-11 Female (Reserved)
RS-232	1 x DB-9 Male (Reserved) 1 x DB-9 Female (Reserved)
Pushbuttons	
Operating Mode Selection	1 x Pushbutton
LEDs	
Local	1 (Green)
Remote	1 (Green)
Emulation	
Keyboard / Mouse	PS/2, USB
Video	Up to 1920 x 1200 @ 60Hz; DDC2B
Power Consumption	DC5.3V:1.96W:16BTU/h  Note: <ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul>
Environmental	
Operating Temperature	0 - 50°C
Storage Temperature	-20 - 60°C
Humidity	0–80% RH, Non-condensing
Physical Properties	
Housing	Metal
Weight	0.49 kg ( 1.08 lb )
Dimensions (L x W x H)	20.30 x 8.64 x 2.50 cm (7.99 x 3.4 x 0.98 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

## Diagram



### **ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their  
 respective owners.