

## CS1182

2-Port USB DVI Secure KVM Switch



The CS1182 is NIAP-certified and passed the Evaluation Assurance Level 2 (EAL2+) requirements for Peripheral Sharing Switch (PSS) for Human Interface Devices (HIDs) Protection Profile v2.1, satisfying the latest security requisites set by the U.S. Department of Defense for peripheral switches. Compliance ensures maximum information security while sharing a single set of HIDs (keyboards, mouse, speakers, etc.) between multiple computers. Conformity with Protection Profile v2.1 certifies that other USB peripherals cannot be connected to the console ports of the CS1182, and that only a keyboard and mouse are accommodated, therefore providing high-level security, protection and safekeeping of data.

Hardware security includes tamper-evident tape, chassis intrusion detection, and tamper-proof hardware, while software security includes restricted USB connectivity — non HIDs (Human Interface Devices) are ignored when switching — an isolated channel per port that makes it impossible for data to be transferred between secure and unsecure computers, and automatic clearing of the keyboard buffer.

By combining physical security with controlled USB connectivity, the CS1182 gives you the means to consolidate multiple workstations of various security classification levels with one keyboard, monitor and mouse (KVM) console.

Note: 1. The National Information Assurance Partnership (NIAP) is a United States government initiative to meet the security testing needs of IT consumers and manufacturers. It is operated by the National Security Agency (NSA) and the National Institute of Standards and Technology (NIST).  
2. The CS1182 additionally satisfies Evaluation Assurance Level 2+ (EAL2+) requirements for Peripheral Sharing Switch (PSS) for Human Interface Devices Protection Profile v2.1.



## Features

- 2-port USB DVI Dual-Link Secure KVM Switch
- [Port selection via Pushbutton only \(OSD, hotkey methods are not allowed\)](#) to enhance security
- One USB console controls 2 secure computers
- [NIAP-certified](#) — validated to [Common Criteria EAL2+](#) security requirements
- [Restricted USB connectivity](#) — non HID's (Human Interface Devices) are ignored when switching
- [Isolated channel per port](#) — makes it impossible for data to be transferred between computers
- [Tamper-evident tape](#) — provides a visual indication of any attempt to gain access to the switch's internal components
- [Chassis intrusion detection](#) — if the cover is removed from the switch, the unit becomes inoperable and the LEDs flash
- [Tamper-proof hardware](#) — all integrated circuits are soldered directly to the circuit board to prevent tampering with the components
- [Non-reprogrammable ROM](#) — prevents tampering and attempts to reprogram the switch's firmware
- [Clears keyboard buffer](#) — keyboard data is automatically cleared after transmission to the switch
- [Video DynaSync™](#) — stores the console monitor's EDID (Extended Display Identification Data) to optimize display resolution
- [Multiplatform support](#) — Windows, Linux, Mac, and Sun
- Superior video quality — 2560 x 1600 (DVI Dual Link); 1920 x 1200 (DVI Single Link) and 2048 x 1536 (DVI-A)
- Rugged metal enclosure
- [Built-in internal power](#)
- Speaker and microphone support

## Specification

|                      |  |
|----------------------|--|
| Computer Connections | 2  |
| Port Selection       | Pushbutton   |
| Connectors           |  |
| Console Ports        | 2 x USB Type-A Female (Black)<br>1 x DVI-I Dual Link Female (White)<br>2 x Mini Stereo Jack Female<br>(Green;1 x front panel,1 x rear panel)<br>2 x Mini Stereo Jack Female (Green;1 x front panel,1 x rear panel) |
| KVM Ports            | 2 x USB Type-B Female (White)<br>2 x DVI-I Dual Link Female (White)<br>2 x Mini Stereo Jack Female (Green)<br>2 x Mini Stereo Jack Female (Pink)   |
| Power                | 1 x 3-prong AC Socket  |
| Switches             |  |
| Port Selection       | 2 x Pushbuttons  |
| Reset                | 1 x Semi-recessed Pushbutton   |
| Power                | 1 x Rocker   |
| LEDs                 |  |
| Power                | 1 (Blue)   |
| Online               | 2 (Green)  |
| Selected             | 2 (Orange)   |
| Emulation            |  |
| Keyboard / Mouse     | USB  |
| Video                | DVI Dual Link: 2560x1600;<br>DVI Single Link: 1920x1200<br>DVI-A: 2048x1536  |

|                            |  |
|----------------------------|--|
| Maximum Input Power Rating | 100–240V AC; 50/60 Hz; 0.5A  |
| Power Consumption          | AC110V:3.4W:31BTU/h<br>AC220V:3.6W:32BTU/h<br><br>Note:<br><ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul> |
| Environmental              |  |
| Operating Temperature      | 0-40°C   |
| Storage Temperature        | -20-60°C   |
| Humidity                   | 0 - 80% RH, Non-condensing   |
| Physical Properties        |  |
| Housing                    | Metal  |
| Weight                     | 2.06 kg ( 4.54 lb )  |
| Dimensions (L x W x H)     | 34.90 x 16.90 x 6.09 cm<br>(13.74 x 6.65 x 2.4 in.)  |
| Note                       | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.  |

#### Diagram





Simply Better Connections

***ATEN International Co., Ltd.***

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.