

VC960

Mini DisplayPort to DVI Adapter









Plug-n-Play

No installation software or drivers required. The VC960 is the perfect solution for connecting Mini DisplayPort inputs to DVI output displays.





Contact Sales

Superior Video Resolution

Supports resolutions up to 1920 x 1200 and 1080p, making it highly compatible across devices.



Talk to Our Experts



If you prefer to have ATEN contact you, please complete the form and a representative will be in touch with you shortly

| First Name * | |
|-------------------|---|
| | |
| Last Name * | |
| | |
| - Country * | • |
| | |
| Company * | |
| | |
| Email * | |
| | |
| Phone Number | |
| | |
| - Customer Type * | - |
| | |
| Job Title * | |
| | |



Features

The Mini DisplayPort to DVI Adapter allows you to connect a device with a Mini DisplayPort to a display with a DVI connector.

The adapter is perfect for Mac series products, including MacBook, MacBook Pro, MacBook Air, Mac mini and Mac Pro.

- Converts Mini DisplayPort signals to DVI output
- Supports VGA, SVGA, XGA, SXGA, UXGA and resolutions up to 1920x1200(PC) / 1080p(HDTV)
- Supports Mac Products including MacBook, MacBook Pro, MacBook Air, Mac mini and Mac Pro
 No software or driver installation needed
- DisplayPort 1.2 compliant

Specification

| Video Input | |
|--------------------------|---|
| Interfaces | 1 x Mini DisplayPort Male (White) |
| Video Output | |
| Interfaces | 1 x DVI-I Female (White)* *VC960 Only supports digital signal transmission. |
| Video | |
| Max. Pixel Clock | 165 MHz |
| Max. Resolution | Input up to 4096 x 2160@60Hz (4:4:4) Output up to 1920 x 1200 |
| Compliance | DP 1.2 |
| Environmental | |
| Operating Temperature | 0 - 50 °C |
| Storage Temperature | -20 - 60 °C |
| Humidity | 0 - 80% RH, Non-Condensing |
| Physical Properties | |
| Housing | Plastic |
| Weight | 0.05 kg (0.11 lb) |
| Dimensions (L x W x H) | 20.00 x 4.30 x 2.01 cm (7.87 x 1.69 x 0.79 in.) |
| Carton Lot | 40 pcs |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |



Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.