

VE602

DVI Dual Link/Audio Cat 5 Extender (2560 x 1600@40m)



The VE602 DVI Dual Link Extender with Audio extends your DVI display up to 60 m away from your DVI source using Cat 5e cables. The use of Cat 5e cables provides a simple and reliable connection method that takes advantage of the wiring system in most modern office buildings.

The VE602 incorporates ATEN's technology that allows A/V signals to be transmitted over one Cat 5e cable. It uses ATEN default EDID, but is able to learn and save the EDID configuration of the remote display. For dual link video signals, simply use a second Cat 5e cable.

With support for stereo audio and popular widescreen video formats, the VE602 provides crystal-clear image and sound quality for installations where remote DVI video displays are required.

Features

- Extends the distance between the DVI source and DVI display device
- Long distance transmission – up to 60 m
- Uses Cat 5e cable to connect the local and remote units
- [Employs ATEN EDID technology that allows signal transmission over one Cat 5e cable](#)
- Uses a second (Sub) Cat 5e cable for dual link signals*
- [Supports EDID Learning – Automatically learns and saves the EDID data of the display to which the Transmitter \(VE602T\) is connected](#)
- Superior video quality – DVI Dual Link up to 2560 x 1600 @ 60 Hz (40 m); DVI Single Link up to 1920x1200 @ 60 Hz (40 m), 1024 x 768 @ 60 Hz (60 m)
- Audio enabled
- 8 segment equalization adjustment switch optimizes display quality
- Built-in 8KV/15KV ESD protection
- Supports widescreen formats
- Rack mountable

Note:

* The length of the two Cat 5e cables must be the same.


** HDCP is not supported.

Specification

Function	VE602R	VE602T
Video Input		
Interfaces	N/A	1 x DVI-D Female (White)
Impedance	N/A	100 Ω

Max. Distance	N/A	1.8 m
Video Output		
Interfaces	1 x DVI-D Female (White)	N/A
Impedance	100 Ω	N/A
Video		
Max. Data Rate	6.75 Gbps (2.25 Gbps Per Lane)	6.75 Gbps (2.25 Gbps Per Lane)
Max. Pixel Clock	225 MHz	225 MHz
Max. Resolutions / Distance	Dual Link: up to 2560 x 1600@40m Single Link: up to 1920 x 1200@40m; 1280 x 1024@60m	Dual Link: up to 2560 x 1600@40m Single Link: up to 1920 x 1200@40m; 1280 x 1024@60m
Audio		
Input	N/A	1 x Mini Stereo Jack Female (Green)
Output	1 x Mini Stereo Jack Female (Green)	N/A
Connectors		
Power	1 x DC Jack	1 x DC Jack
Power Consumption	DC5.3V:2.4W:11BTU	DC5.3V:2.86W:13BTU
Environmental		
Operating Temperature	0 - 50°C	0 - 50°C
Storage Temperature	-20 - 60°C	-20 - 60°C
Humidity	0 - 80% RH, Non-Condensing	0 - 80% RH, Non-Condensing
Physical Properties		
Housing	Metal	Metal
Weight	0.18 kg (0.4 lb)	0.18 kg (0.4 lb)
Dimensions (L x W x H)	9.13 x 5.60 x 2.40 cm (3.59 x 2.2 x 0.94 in.)	9.13 x 5.60 x 2.40 cm (3.59 x 2.2 x 0.94 in.)
Carton Lot	20 pcs	20 pcs
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.	

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their
 respective owners.