

VS102

2-Port VGA Splitter Wall Plate (250MHz)



VS102 video splitters provides video input signals to 2 video outputs each at 250 MHz after duplication. Users can boost video signals from the video gain knob within a transfer range up to 65m.



Features

- One video input to 2 video outputs.
- Cascadable to 3 levels-provides up to 8 video signals.
- Supports up to 250 MHz bandwidth.
- Long distance transmission - up to 65 m. *
- High video resolution - up to 1920 x 1440.
- DDC, DDC2, DDC2B Compatible (Port 1 only).
- Supports VGA, XGA, SVGA, UXGA and multisync monitors.
- OS Support: Windows 2000, Windows XP, Linux, Mac and Sun
- Compact design with convenient topside connection, lays flat on a desktop or mounts on the wall

* Video content sent over very long distance using a VGA cable might result in slight degradation of the video signal and quality.

Specification

2-Port Video Splitter

Video Input	
Interfaces	1 x HDB-15 Male (Blue)
Impedance	75 Ω
Max. Distance	1.8 m
Video Output	
Interfaces	2 x HDB-15 Female (Blue)
Impedance	75 Ω
Video	
Max. Bandwidth	250 MHz
Max. Resolution	Up to 1920 x 1440
Max. Distance	Up to 65 m
Connectors	
Power	1 x DC Jack
Power Consumption	DC9V:1.22W:6BTU
Environmental	
Operating Temperature	0-50 °C
Storage Temperature	-20 - 60 °C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Metal
Weight	0.19 kg (0.42 lb)
Dimensions (L x W x H)	10.36 x 7.90 x 2.82 cm (4.08 x 3.11 x 1.11 in.)
Carton Lot	20 pcs
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their
respective owners.