

## VS201

2-Port VGA Switch Wall Plate



The VS201 Video Auto Switch is an automatic video switch that is ideal for monitors using analog signals. In addition, the VS201 boosts signals, allowing long distance transmission of up to 65 m (210 feet).

A slide switch sets the priority for the incoming video signals for display on the monitor, and the VS201 automatically selects the proper input signal for its output port. Both features make the VS201 an excellent choice for educational environments.

**RS-232  
Control**

**VDS** Video  
DynaSync



**Video In**

**HDB-15**



**Video Out**

**HDB-15**



**Stereo  
Audio**

## Features

- Displays the video output of two computers on a single monitor or projector
- Automatic incoming signal selection (Auto)
- Quick and easy switching via slide switch
- Long-distance transmission – up to 65 m \*
- Superior video quality – up to 1920 x 1440
- Supports VGA, XGA, SVGA, UXGA and multisync monitors

\* Video content sent over very long distance using a VGA cable might result in slight degradation of the video signal and quality.

## Specification

Video Input	
Interfaces	2 x HDB-15 Male (Blue)
Impedance	75 $\Omega$
Max. Distance	1.8 m
Video Output	
Interfaces	1 x HDB-15 Female (Blue)
Impedance	75 $\Omega$
Max. Distance	30 m
Video	
Max. Bandwidth	300 MHz
Max. Resolution	Up to 1920 x 1440
Max. Distance	Up to 30 m
Connectors	
Power	1 x DC Jack
Power Consumption	DC5V:0.75W:4BTU/h  Note: <ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul>
Environmental	
Operating Temperature	0 - 50°C
Storage Temperature	-20 - 60°C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Metal
Weight	0.20 kg ( 0.44 lb )
Dimensions (L x W x H)	10.36 x 7.90 x 2.79 cm (4.08 x 3.11 x 1.1 in.)
Carton Lot	20 pcs
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

## Diagram



### ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their  
 respective owners.