

# **VS431**

### 4-Port HDTV A/V Switch



The 4 port VS431 makes plugging and unplugging devices a thing of the past. This high quality component video (YPbPr) switche with on-board stereo audio is perfect for HDTV enthusiasts who want to add more inputs to their high-definition display. Use the VS431 to effortlessly connect a DVD player and set-top box or satellite receiver to your HDTV or projector.

Or, for the home theatre buff, the VS-431 provides a complete switching solution. The IR remote is an added convenience, allowing you to enjoy multimedia switching from the comfort of your seat. The VS431 HDTV switche supports high-end digital video devices such as DVD players and recorders, set-top boxes, satellite receivers, and more. It also works well for high-definition editing systems.

#### **Features**

- Displays the video output of four digital devices on a single high definition monitor or projector.
- · Stereo audio support.
- Quick and easy switching via front panel pushbuttons or IR remote control.
- Electronic switching for greater reliability and durability.
- Easy installation.
- Complete home theater switching solution.

#### **Specification**


| Device Connections | 4  |
|--------------------|--|
| Port Selection     | Push Buttons,IR Remote Control   |
| Connectors         |  |
| Input              | 4 x RCA Female (Green) 4 x RCA Female (Blue) 4 x RCA Female (Red) 4 x RCA Female (White) |
| Audio              | 4 x RCA Female (Red) 1 x RCA Female (White) 1 x RCA Female (Red)                         |
| Output             | 1 x RCA Female (Green)   |
| Video              | 1 x RCA Female (Blue) 1 x RCA Female (Red)   |



|                          | 4 70 1 1 (7) 1)  |  |
|--------------------------|--|--|
| Power                    | 1 x DC Jack (Black)  |  |
| Switches                 |  |  |
| Power                    | 4 x Pushbutton   |  |
| LEDs                     |  |  |
| Online                   | 4 (Orange)   |  |
| Selected                 | 4 (Green)  |  |
| Power Consumption        | DC 5.3V, 0.8W (Max.)   |  |
|                          | Note:  The measurement in Watts indicates the typical power consumption of the device with no external loading.  The measurement in BTU/h indicates the power consumption of the device when it is fully loaded. |  |
| Video                    | 1600 x 1200 @ 60Hz;<br>480p, 720p, 1080i, 1080p  |  |
| Environmental            |  |  |
| Operating<br>Temperature | 0-50°C   |  |
| Storage<br>Temperature   | -20-60°C   |  |
| Humidity                 | 0 - 80% RH, Non-Condensing   |  |
| Physical Properties      |  |  |
| Housing                  | Metal  |  |
| Weight                   | 0.85 kg  |  |
| Dimensions (L x W x H)   | 26.00 x 7.66 x 4.40 cm   |  |
| Note                     | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.  |  |



### Diagram



## ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.