

## WMPII-SD-L

10U/12U/15U Wall Mount Rack



With more than 30 years of experience in R&D and manufacturing cabinet products, ATEN can tailor exclusive products for its customers based on their needs. Our cabinet products, all of which are extremely popular, have been certified by UL and by CE. All ATEN's rack products are EIA/ECA-310-E compliant. Our high-quality cabinets have multiple patents numbered: M377678, M385174, and M513193.

ATEN wall mount racks use a suspended design, and can be affixed on the walls of buildings. This makes them suitable for locations with limited space or when they need to be placed higher up on the wall, such as piping rooms in buildings, classrooms, and train platforms. The cabinets are sturdily built and are equipped with a 120V/230V AC fan, which prevents equipment malfunctions caused by overheating in the rack.

### Features

#### • Sturdy Structural Design

- Designed to be installed off the ground, solving the issues of limited space or difficult cabling
- Made from bent SPCC steel, maximum capacity of 50kg
- Cable holes are provided on both sides of the rack for easier cabling
- 45° heat dissipation holes are provided on the front of the top and bottom of the rack, for maximum heat dissipation and convection while not damaging the external aesthetics
- Comes with a fan (120V/230V AC) on the top of the rack as standard, providing faster heat dissipation and protecting the equipment from malfunctions
- Holes are provided on the left and right sides of the back of the rack for hanging, and wall plugs are provided for easy installation

#### • Certifications

- UL Certified and CE Certified
- Compatible with the latest specification of EIA/ECA-310-E

#### • Includes

- WMPII-SD-L wall mount rack enclosure frame × 1 pc
- Acrylic front door (with door lock and key) × 1 pc
- 120V /230V AC Fan × 1 pc
- M5 Mounting Screw × 20 pcs
- Cage nut × 20 pcs
- Expansion bolt × 4 pcs

## Specification

|                         |                    |                    |                    |
|-------------------------|--------------------|--------------------|--------------------|
| Function                | WMP11-106056-19    | WMP11-126056-19    | WMP11-156056-19    |
| Part Number             | YGAS-106056-001    | YGAS-126056-001    | YGAS-156056-001    |
| Physical Properties     |                    |                    |                    |
| Rack Height (U Spaces)  | 10U                | 12U                | 15U                |
| Internal Height         | 448 mm             | 537 mm             | 671 mm             |
| Overall Height          | 508 mm             | 597 mm             | 731 mm             |
| Overall Depth           | 600 mm             | 600 mm             | 600 mm             |
| Overall Width           | 560 mm             | 560 mm             | 560 mm             |
| Color                   | White              | White              | White              |
| Enclosure Frame         | SPCC               | SPCC               | SPCC               |
| 19" EIA Rails           | SPCC               | SPCC               | SPCC               |
| Door Type               | Acrylic Front Door | Acrylic Front Door | Acrylic Front Door |
| Weight Loading (Static) | 50 kg              | 50 kg              | 50 kg              |
| Fan Type                | 120 VAC / 230VAC   | 120 VAC / 230VAC   | 120 VAC / 230VAC   |

### ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their respective owners.