

FH300

3-Port FireWire Hub



The FH300 IEEE 1394 Hubs provide three 1394a compliant ports that support data transfer rates of 100, 200, and 400 Mbps. Each port automatically switches to the highest speed that the peripheral supports. Each IEEE 1394 peripheral connects externally; simply plug in the cables. Configuration is automatic; there is no need to specify memory addresses, IRQ assignments, device IDs, or even plug in terminators. The advantages of hot pluggable connectivity and non interrupting daisy chaining has distinguished FireWire as a household standard.



Features

- 3 IEEE 1394 ports for more convenient adding and removing of devices.
- IEEE 1394, IEEE 1394a Compliant.
- 100, 200, 400 Mbps data transfer rate; automatically uses the highest speed the peripheral supports.
- Supports hot plugging.
- 6 pin IEEE 1394 I/O connectors.
- DC input terminal for optional external power supply.
- OS Support: Windows 2000, Windows XP, Mac and FreeBSD

Specification

Ports	3
Connectors	
USB Port	3 x 6 pin IEEE 1394 Std. (Black)
Power	1 x DC Jack (Black)
LEDs	1 (Orange)
Data Rate	100 / 200 /400 Mbps (Asynchronous, Isochronous)
Standard Support	IEEE 1394a
Power Consumption	DC 9V, 0.15W
Environmental	
Operating Temperature	5°-40°C
Storage Temperature	-20°-60°C
Humidity	0 ~80% RH, Non-condensing
Physical Properties	
Housing	Plastic
Weight	0.07 kg (0.15 lb)
Dimensions (L x W x H)	7.76 x 7.02 x 3.12 cm (3.06 x 2.76 x 1.23 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their
respective owners.