

UE2120H

12 m 4-Port USB 2.0 Extender Cable (Daisy-chaining up to 60 m)



The UE2120H allows users to extend the distance between a computer and USB device(s) up to 12 meters via the active extender hub. USB signals transmitted through these cables maintain optimal signal integrity and meet USB 2.0 standards. Up to 4 extender cables ([UE2120](#)) and 1 Extender Hub (UE2120H) can be chained together, so that cable distance is increased by up to 60 meters.

12m

**Long
Distance
Transmission**



USB 2.0



**Daisy-
Chain**



**Bus-
Powered**

Features

- Extends the distance to your USB device(s) up to 12 meters (36')
- 4 Downstream USB 2.0 ports
- USB specification version 2.0 / 1.1 compliant
- Plug and play - No additional driver required
- Up to 4 extender cables (UE2120) and 1 Extender Hub (UE2120H) can be chained for a distance of up to 60 meters
- Bus powered. No power adapter required
- Multiplatform support – Windows, Mac

Specification

| | |
|------------------------|---|
| Connectors | |
| USB Port | 1 x USB Type-A Male |
| Downstream | 4 x USB Type-A Female |
| Power | 1 x DC 5V (Optional) |
| LEDs | 1 (Green) |
| USB Specification | 2.0 / 1.1 For High / Full / Low Speed |
| Cable Length | 12 m |
| Environmental | |
| Operating Temperature | 0–40°C |
| Storage Temperature | -20–60°C |
| Humidity | 0–80% RH |
| Physical Properties | |
| Housing | Plastic |
| Weight | 0.63 kg (1.39 lb) |
| Dimensions (L x W x H) | 8.20 x 4.10 x 1.70 cm (3.23 x 1.61 x 0.67 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.