

2L-7DA3H

0.3 m High Speed HDMI Cable with Ethernet



ATEN High Speed HDMI Cable with Ethernet provides an uncompressed, all-digital interface for both audio and video signals, guaranteeing reliable digital signal transmission up to 4K (4096 x 2160 / 3840 x 2160 @ 30 Hz). Our cables infuse high-quality tinned copper wire to resist interference for better- defined video and image quality.



Features

- Optimum signal transmission up to 4K (4096 x 2160 / 3840 x 2160 @ 30 Hz) and standard 1920 x 1080 @ 60 Hz
- HDMI Ethernet Channel functionality: additional dedicated data channel supports networking*
- HDMI (3D, Deep Color, 4K); HDCP 2.2 compliant
- Gold-plated connectors for reliable transmissions
- Available in 0.3 m
- Bend Radius 90° **

Note:

* Feature only available if linked devices are HDMI Ethernet Channel enabled

** Swings 100 times between angles of +/- 90 degrees, at a frequency of 13 times per minute

Specifications

Video Resolution	Up to 4096X2160 @30Hz
Physical Properties	
Cable Length	0.3m
Cable Color	Black
Cable Outer Dimension	6.0 +- 0.15mm
Conductor Gauge	30AWG
Conductor Material	Tinned Copper
Connector Plating	Gold
Connector Type	HDMI (19pin) Male to Male
Cable Shield Type	Aluminum Foil
Cable Jacket Type	PVC
Environmental	
Operating Temperature	80°C
Rating	UL VW-1 (Flame rate), CSA
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.