


VS5812

2-Port 8K HDMI Splitter








Superior Video

3D | Deep Color | HDR10+ | Dolby Vision®

Premium Audio

DTS-HD Master Audio™ | DTS:X® Dolby® TrueHD | Dolby Atmos®









iko III. Die 7-54 OMEN Igilmegjeun die Ahruinseicher (had priemter im augheren bahe dettp. Fragen; ahru), mie Geben berig, he Wiis II b De politicher bepreim kan beine, lighete patej auch deut deut die sei ausmal Wertender die gespannte II priemes De planende III auf Wiis de VIII state mater der deut deut being de ont de man bendady dapane auf priese Francy III iza De planende III auf Wiis Sestande hat beiter del was. Hyp wit kille wied alt what selvings, appart by Millik, Enly Wins Wiis The Mark (had














Dive in. Game on.

Enjoy ultra-smooth, responsive gameplay.



VRR Variable Refresh Rate

Automatic Low Latency Mode







Up to 48 Gbps Ultra High Speed Video Transmission



Broad Device Compatibility

Works with a wide range of input and output devices









































Talk to Our Experts

If you prefer to have ATEN contact you, please complete the form and a representative will be in touch with you shortly

First Name *	
Last Name *	
- Country *	•
Company *	
Email *	
Phone Number	
- Customer Type *	_
Job Title *	

















Features

- EDID SyncTM Smart Display Optimization
 Automatically optimizes resolutions and prevents display issues for flawless display presentation
- Extreme Dual-Display Resolution Distribution
 Shares one HDMI source across two displays, delivering simultaneous 8K @ 60Hz and 4K @ 120Hz visuals
- Variable Refresh Rate (VRR)
 Synchronizes frame rate to eliminate screen tearing and stutter for ultra-smooth gameplay
- Auto Low Latency Mode (ALLM)
 Automatically switches to game mode, dramatically reducing input lag for responsive control
- HDMI 3D/Deep Color, HDR10+, HDCP 2.3 Compatible
 Guarantees stable performance, broad compatibility, and superior image quality

- Pushbutton Output Control
 Instantly enables or disables HDMI out 2 with a press of the pushbutton for intuitive, hands-on display management
- Aesthetic Compact Form
 Slim profile and stylish accent lighting allow integration into any space, perfectly complementing your setting




Specifications

Specifications	
Video Input	
Interfaces	1 x HDMI Type A Female (Black)
Impedance	100 Ω
Max. Distance	Max 1.5m at 7680x4320 @ 60Hz (4:2:0)
Video Output	
Interfaces	2 x HDMI Type A Female (Black)
Impedance	100 Ω
Max. Distance	Max 1.5m at 7680x4320 @ 60Hz (4:2:0)
Video	
Max. Data Rate	48 Gbps
Compliance	HDMI (3D, Deep Color, 8K) HDCP 2.3 Compatible
Max. Resolution	7680x4320 @ 60Hz (4:2:0)
Audio	
Input	1 x HDMI Type A Female (Black)
Output	2 x HDMI Type A Female (Black)
Connectors	
Power	1 x USB-C (5V/1A)
Cable Length	
USB Cable	1 x USB Type-C to Type-A (1m)
LEDs	
LED Indicator	2 x Port Indicator (Orange)
Power	2 (Orange, Bottom Side)
Environmental	
Operating Temperature	0-40 °C
Storage Temperature	-20 - 60 °C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	PC PC
Weight	0.03 kg (0.07 lb)
Dimensions (L x W x H)	6.10 x 56.50 x 1.52 cm (2.4 x 22.24 x 0.6 in.)
Carton Lot	20 pcs
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.



Diagram





ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com



Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.