

VS5821

2-Port 8K HDMI Switch






























Ngaringer fining apainer aft in 1922, alfred Mill Inlin approach in the real paraller II (in Mi painters in this parall minimus and palating fining fining and paraller fining fining and paraller parallers, but a standard fining fining and an interpretation of the parallers, but an interpretation of the parallers and shower the parallers and shower and an approach with the parallers and shower and an approach with the parallers and shower a significant and the parallers and th














Dive in. Game on.

Enjoy ultra-smooth, responsive gameplay.



VRR Variable Refresh Rate

Automatic Low Latency Mode







Up to 48 Gbps
Ultra High Speed Video Transmission




One-Button Switch 2-to-1 RapidSync™































Talk to Our Experts

If you prefer to have ATEN contact you, please complete the form and a representative will be in touch with you shortly

First Name *	
Last Name *	
- Country *	•
Company *	
Email *	
Phone Number	
- Customer Type *	_
Job Title *	

















Features

- RapidSync™ High-Speed AV Switching
 Ensures instant synchronization and ultra-fast transitions, eliminating signal delay
- Ultra-High Resolution Visuals
 Delivers 8K @ 60Hz and 4K @ 120Hz for exquisite clarity and unparalleled realism
- Variable Refresh Rate (VRR)
 Synchronizes frame rate to eliminate screen tearing and stutter for ultra-smooth gameplay
- Auto Low Latency Mode (ALLM)
 Automatically switches to game mode, dramatically reducing input lag for responsive control
- HDMI 3D/Deep Color, HDR10+, HDCP 2.3 Compatible
 Guarantees stable performance, broad compatibility, and superior image quality

- Instant Source Switching
 Easily switches between two HDMI sources via pushbutton for quick, hands-on control
- Aesthetic Compact Form
 Slim profile and stylish accent lighting allow integration into any space, perfectly complementing your setting



Specifications


Specifications	
Video Input	
Interfaces	2 x HDMI Type A Female (Black)
Impedance	100 Ω
Max. Distance	1.5m at 7680x4320 @ 60Hz (4:2:0)
Video Output	•
Interfaces	1 x HDMI Type A Female (Black)
Impedance	100 Ω
Max. Distance	1.5m at 7680x4320 @ 60Hz (4:2:0)
Video	-
Max. Data Rate	48 Gbps
Compliance	HDMI (3D, Deep Color, 8K) HDCP 2.3 Compatible
Max. Resolution	7680x4320 @ 60Hz (4:2:0)
Audio	
Input	2 x HDMI Type A Female (Black)
Output	1 x HDMI Type A Female (Black)
LEDs	•
Selected	2 x Port Selector (Orange)
Power	2 (Orange, Bottom Side)
Connectors	
Power	1 x USB-C (5V/1A)
Cable Length	
USB Cable	1 x USB Type-C to Type-A (1m)
Environmental	-
Operating Temperature	0-40 ℃
Storage Temperature	-20 - 60 °C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	PC PC
Weight	0.03 kg (0.07 lb)
Dimensions (L x W x H)	6.10 x 56.50 x 1.52 cm (2.4 x 22.24 x 0.6 in.)
Carton Lot	20 pcs
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.




Diagram

F Ac









ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com



Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.