

PE0209S

Basic 1U PDU with surge protection

PE0209SG



The Aten's PE0209S, a 9-outlet, 1U rack mount power distribution unit ([PDU](#)), provides IEC and NEMA output. It distributes power to 9 receptacles from a single plug with unfiltered electrical pass-through. The PE0209S also provides surge protection, prevents damage to your equipment from power surges and spikes. The integrated surge protector includes a LED indicator, letting you know the status of your equipment.

Note: The warranty does not cover any accessories external to the product like the surge protection module.

Features

- Space saving -1U rack mount design
- IEC or NEMA outlet models
- Surge Protection
- Aluminum material
- Works with [data centers](#), server rooms and telecom equipment

Specifications

Electrical	
Nominal Input Voltage	100-240 VAC
Maximum Input Current	16A (Max)
Input Frequency	50-60 Hz
Input Connection	For G Plug: IEC-320 C20 For Z Plug: Chinese 16A
Input Power	3680VA(Max)
Outlet Type	(8)IEC C13+(1)IEC C19
Maximum Output Current (Outlet)	IEC C13:10A Max IEC C19:16A Max
Maximum Output Current (Bank)	16A (Max)
Maximum Output Current (Total)	16A (Max)
OPD(Overcurrent Protection Device)	Yes
Physical Properties	
Dimensions (L x W x H)	48.20 x 4.44 x 4.50 cm (18.98 x 1.75 x 1.77 in.)
Weight	0.67 kg (1.48 lb)
Power Cord Length	10ft(3x2.5mm2)
Environmental	
Temperature (Operating / Storage)	0 – 40°C / -20 – 60°C *When the environmental temperature comes close 40 degrees, it is recommended to lower the load to 60% to comply to the safety regulations.
Elevation (Operating / Storage)	3000m
Compliance	
EMC Verification	-
Safety Verification	LVD
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram**ATEN International Co., Ltd.**

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their
respective owners.