Simply Better Connections

# RS47U100

RS Series Standing Network Rack



ATEN Racks are designed for mounting standard 19" rackmount equipment – servers, routers, UPS systems, switches, audio/video devices – regardless of brand. All racks provide straightforward equipment organization, excellent security and simple cable management while enabling optimum airflow. To simplify deployment, ATEN Racks comes with casters and leveling feet. The casters allow ATEN Racks to be easily maneuvered into the desired location, where it can then be secured in place by adjusting the leveling feet. The RS Series Rack contains a locking, reversible, removable front door that is perforated to promote efficient airflow, as well as locking, removable solid side panels. Locking doors and side panels prevent unauthorized access to installed equipment. The RS Series Rack provides standard features for a more cost-effective rack solution.

### Features

- ## High Ventilation Hexagonal Perforation
  - Hexagonal perforated front and back doors provide higher tensile strength than round holes while ensuring efficient airflow and optimized ventilation

- ## More Space for Cable Management
  - Vertical cable management rail design in 800mm wide rack provides more space for network cable management

- ## High Loading Capacity
  - Static loading capacity up to 800KG

### Specifications

| Physical Properties | |
|---|---|
| Rack Height (U Spaces) | 47U |
| Type | Rack Enclosure |
| Package Contents | "Build-Up(Default)<br>Knock-Down(Special Requirement) " |
| Mounting Hole Type | Square |

| | |
|---|---|
| Color | Black |
| Unit Dimensions(H*W*D) | 2277 x 600 x 1000 |
| Maximum Device Height | 2277 |
| Maximum Device Width | 600 |
| Maximum Device Depth | 1000 |
| Max/Min/Default Mounting | 890/200/700 |
| Maximum Mounting | 890 |
| Minimum Mounting | 200 |
| Default Mounting | 700 |
| Shipping Dimensions : Build-Up ( H x W x D) | 620 x 1020 x 2290 |
| Shipping Dimensions : Knock-Down ( H x W x D) | Package1 : 2205 x 620 x 320<br>Package2 : 620 x 1020 x 130<br>Package3 : 2135 x 60 x 730 |
| Shipping Weight | 120 |
| Unit weight | 115 |
| Weight capacity stationary | 800 |
| Weight capacity dynamic | 600 |
| Material | SPCC Cold Rolled Steel |
| Air permeability | 0.65 |
| Certifications | |
| Approvals | CE |
| Certifications | RoHS |
| Protection class | IP20 |
| Shipping | |
| Build-Up packing Unit volume (CBM) | 1.45 |
| Knock-Down packing Unit volume (CBM) | Package1 : 0.44<br>Package2 : 0.08<br>Package3 : 0.09 |
| Build-up package (20GP) | 23 |
| Build-up package (40GP) | 49 |
| Build-up package (40HQ) | 49 |
| Knock-Down package (20GP) | 47 |
| Knock-Down package (40GP) | 95 |
| Knock-Down package (40HQ) | 112 |

Simply Better Connections

**ATEN International Co., Ltd.**
3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com

© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.