

CS62U

2-Port USB VGA/Audio Cable KVM Switch (1.8m)



CS62U 2-Port USB KVM Switch has a handy design integrating with 1.8m of cables. It can control 2 servers via a single console.



Features

- One USB console controls two USB computers
- Compact design, built-in 1.8 m cables
- Hotkey selection for OS and keyboard language
- [Computer Selection via hotkey and USB mouse](#) **NEW!**
- Multiplatform support - Windows, Linux, Mac, Sun
- [Video DynaSync™](#) - exclusive ATEN technology eliminates boot-up display problems and optimizes resolution when switching between ports
- [Console mouse port emulation/bypass feature supports most mouse driver](#) **NEW!**
- [USB mouse port can be used for USB hub and USB peripheral sharing](#) *
- [Supports gaming keyboards](#) **NEW!**
- [Supports multifunction and wireless keyboards and mice](#) **NEW!**
- All-in-one design
- With speaker support
- Superior video quality – up to 2048 x 1536; DDC2B
- Auto Scan function to monitor computer operation
- Non-powered
- Sun/Mac keyboard support and emulation*

- * 1. PC keyboard combinations emulate Sun/Mac keyboards
 2. Sun/Mac keyboards only work with their own computers

Specifications

2-Port USB KVM Switch

| | |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Computer Connections | 2 |
| Port Selection | Hotkey, Mouse |
| Connectors | |
| Console Ports | 1 x HDB-15 Female (Blue) 2 x USB Type A Female 1 x 3.5mm Audio Jack Female (Green) |
| KVM Ports | 2 x HDB-15 Male (Blue) 2 x USB Type A Male 2 x 3.5mm Audio Jack Male (Green) |
| LEDs | |
| Selected | 2 (Green) |
| Cable Length | |
| Computer | 1.8 m |
| Emulation | |
| Keyboard / Mouse | USB |
| Video | 2048 x 1536 @ 60Hz; DDC2B |
| Scan Interval | 5 seconds |
| Environmental | |
| Operating Temperature | 0 - 50°C |
| Storage Temperature | -20 - 60°C |
| Humidity | 0-80% RH, Non-condensing |
| Physical Properties | |
| Housing | Plastic |
| Weight | 0.37 kg (0.81 lb) |
| Dimensions (L x W x H) | 8.75 x 6.08 x 2.80 cm (3.44 x 2.39 x 1.1 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.