

CS64US

4-Port USB VGA/Audio Cable KVM Switch (0.9m, 1.2m)



The CS64US takes a giant step forward from prior cable KVM models in the Petite series, by offering built-in cables, USB peripheral sharing, and a firmware upgrade function that allows you to keep up with latest available versions.

Furthermore, the CS64US features enhanced Video DynaSync™ technology, which stores the console monitor's EDID (Extended Display Identification Data) to optimize display resolution. The CS64US also offers multiplatform support and computer selection via hotkeys to provide the ultimate in desktop convenience.



Features

- One USB console controls four USB computers
- Compact design, built-in 0.9/1.2 m cables
- Hotkey selection for OS and keyboard language
- Computer Selection via hotkey
- Multiplatform support - Windows, Linux, Mac, Sun
- [Video DynaSync™ - exclusive ATEN technology eliminates boot-up display problems and optimizes resolution when switching between ports](#)
- [USB mouse port can be used for USB 1.1 hub and USB 1.1 peripheral sharing](#)
- [Supports multifunction and wireless keyboards and mice](#) **NEW!**
- All-in-one design
- With speaker support
- Superior video quality – up to 2048 x 1536; DDC2B
- Auto Scan function to monitor computer operation
- Non-powered
- Sun/Mac keyboard support and emulation*
- [Firmware upgradable](#) **NEW!**

* 1. PC keyboard combinations emulate Sun/Mac keyboards
2. Sun/Mac keyboards only work with their own computers

Specifications

4-Port USB KVM Switch

| | |
|------------------------|---|
| Computer Connections | 4 |
| Port Selection | Hotkey |
| Connectors | |
| Console Ports | 1 x HDB-15 Female (Blue) 2 x USB Type A Female 1 x 3.5mm Audio Jack Female (Green) |
| KVM Ports | 4 x HDB-15 Male (Blue) 4 x USB Type A Male 4 x 3.5mm Audio Jack Female (Green) |
| LEDs | |
| Selected | 4 (Green) |
| Cable Length | |
| Computer | 2 x 0.9 m; 2 x 1.2 m |
| Emulation | |
| Keyboard / Mouse | USB |
| Video | 2048 x 1536; DDC2B |
| Scan Interval | 1-99 secs. (default 5 secs.) |
| Environmental | |
| Operating Temperature | 0 - 50°C |
| Storage Temperature | -20 - 60°C |
| Humidity | 0-80% RH, Non-condensing |
| Physical Properties | |
| Housing | Plastic |
| Weight | 0.58 kg (1.28 lb) |
| Dimensions (L x W x H) | 9.41 x 9.72 x 2.60 cm (3.7 x 3.83 x 1.02 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.