

BP24V18AH

External Battery Pack for OL1000LV / OL1000HV



ATEN UPS External Battery Pack extends battery runtime when used with ATEN UPS systems. Users will have an extra time to save valuable data from any unexpected power shutdowns.


Note: When the battery pack is not in use, please recharge it for 4 ~ 6 hours every 3 ~ 6 months.

Specifications

| | |
|-----------------------------------|---|
| Electrical | |
| Nominal Input Voltage | 24V |
| Nominal Output Voltage | 24V |
| Maximum Output Current (Total) | 50A Max |
| Battery | |
| Battery Type | Sealed Lead-Acid |
| Battery Size | 12V/9Ah |
| Battery Quantity | 4 |
| Physical Properties | |
| Rack Unit | 2U |
| Dimensions (L x W x H) | 43.80 x 38.00 x 8.60 cm (17.24 x 14.96 x 3.39 in.) |
| Weight | 17.10 kg (37.67 lb) |
| Environmental | |
| Temperature (Operating / Storage) | 0 – 40 °C/-15 – 45 °C |
| Humidity (Operating & Storage) | 0 – 90% (non-condensing) |
| Elevation (Operating / Storage) | 10,000 ft (3,000 m)/50,000 ft (15,000 m) |
| Certifications | |
| Certifications | UL,CE |
| Approvals | RoHS Compliant |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.