

PE1209

Basic Metered 1U PDU

PE1209A



Engineered to enhance the efficiency of power distribution and power status monitoring in an IT environment, the ATEN Basic Metered [PDU](#) Series contains 1U members with 9 outlets and is available in IEC or NEMA socket configurations. The compact form factor plus the support for rack mount installation helps to save space and eliminates clutter.

To monitor the power status of the connected devices, the units feature dual 3-digit 7-segment displays to show the input voltage and output current in real-time. The Basic Metered [PDUs](#) provide secure, centralized power usage of [data center](#) IT equipment, including servers, storage systems, KVM switches, network devices, to optimize power consumption and asset management.

Features

- Space saving 1U rack mount design
- IEC or NEMA outlet models
- Dual 3-digit 7-segment displays to show current and voltage
- Real-time [PDU](#) current monitoring when used in conjunction with the [EC1000 Energy Box](#)

Specifications

| Function | PE1209A | PE1209B | PE1209G |
|------------------------------------|---|---|---|
| Electrical | | | |
| Nominal Input Voltage | 100-120 VAC | 100-240 VAC | 100-240 VAC |
| Maximum Input Current | 20A Max (UL de-rated 16A Max) | 20A Max (UL de-rated 16A Max) | 16A Max |
| Input Frequency | 50-60 Hz | 50-60 Hz | 50-60 Hz |
| Input Connection | For A Plug: NEMA L5-20P For A2 Plug: NEMA 5-20P | NEMA L6-20P | IEC-320 C20 |
| Input Power | 2400VA(Max); 1920VA (UL de-rated) | 4800VA(Max); 3840VA (UL de-rated) | 3840VA(Max) |
| Outlet Type | (9) NEMA 5-20R | (9) IEC 320 C13 | (9) IEC 320 C13 |
| Maximum Output Current (Outlet) | 20A Max (UL de-rated 16A Max) | 15A Max (UL de-rated 12A Max) | 10A Max |
| Maximum Output Current (Bank) | 20A Max (UL de-rated 16A Max) | 20A Max (UL de-rated 16A Max) | 16A Max |
| Maximum Output Current (Total) | 20A Max (UL de-rated 16A Max) | 20A Max (UL de-rated 16A Max) | 16A Max |
| OPD(Overcurrent Protection Device) | Yes | Yes | Yes |
| Physical Properties | | | |
| Dimensions (L x W x H) | 48.20 x 4.44 x 6.00 cm (18.98 x 1.75 x 2.36 in.) | 48.20 x 4.44 x 6.00 cm (18.98 x 1.75 x 2.36 in.) | 48.20 x 4.44 x 6.00 cm (18.98 x 1.75 x 2.36 in.) |
| Weight | 0.80 kg (1.76 lb) | 0.80 kg (1.76 lb) | 0.80 kg (1.76 lb) |
| Power Cord Length | 10ft(12#) | 10ft(12#) | 10ft(3x1.5mm2) |
| Environmental | | | |
| Temperature (Operating / Storage) | 0 – 40°C / -20 – 60°C | 0 – 40°C / -20 – 60°C | 0 – 40°C / -20 – 60°C |
| Elevation (Operating / Storage) | 3000m | 3000m | 3000m |
| Compliance | | | |
| EMC Verification | FCC Class A | FCC Class A | CE Class A |
| Safety Verification | UL, other by request | UL, other by request | CE,LVD, UL |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. | | |

Diagram



Note: As there are many Basic Metered PDUs, PE1324S (top) and PE1118S (bottom) are the respective 0U and 1U examples used here.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.