

VK224

4-Port Serial Expansion Box



The VK224 provides Ethernet-to-serial connectivity with 4 bi-directional RS-232 / 422 / 485 serial ports. It allows users to remotely access serial devices from a PC or any system located anywhere. The complete Telnet CLI commands are fully integrated into users' commercial and industrial applications.

What's more, the VK224 serves as a flexible expansion box of the [ATEN Control System](#), enabling users to control additional serial devices through an ATEN controller in any environments where more serial devices are required. With the advantage of Ethernet-based connection, the expansion box can be easily connected to controllers via LAN connection from a variety of locations across a network.

Accessories:

*The power adapter for this product is sold separately. For more information about this accessory, see [Accessories](#).


Features

- An Ethernet-to-serial box ships with 4 bi-directional RS-232/422/485 serial ports
- Supports Power over Ethernet (PoE) or DC power supply
- Supports IEEE 802.1x authentication protocol for enhanced network security
- Supports Modbus protocol - enables integration with Modbus devices, including TCP, RTU and its checksum data
- Supports Telnet CLI (command-line interface) mode for third-party system integration
- WebUI provides VK224 system information, including firmware upgrade
- An expansion solution for connecting more serial devices to [ATEN Control System](#)
- Flexible deployment via Ethernet connection
- Works with a connected ATEN controller with ID Switch through instant configuration

Specifications

Interfaces			
Serial	<ul style="list-style-type: none">• 4 x Programmable Bi-directional RS-232/422/485 Port (4 x DB9 Male Connector, configurable via pin assignments);<ul style="list-style-type: none">– Baud Rate: 300 to 115200 (default: 9600);– Data Bit: 8 (default) or 7;– Stop Bit: 1 (default) or 2;– Parity: None (default), Even or Odd;– Flow Control: None (default) RTS/CTS		
	RS-232	RS-422	RS-485
	Pin2: RX	Pin 1:RX-	Pin3:D+
	Pin3: TX	Pin 2: RX+	Pin 4:D-
	Pin 5: GND	Pin 3: TX+	Pin 5: GND*
	Pin 7: RTS	Pin 4: TX-	Note: A ground terminal connection is recommended but not required.
	Pin 8: CTS	Pin 5: GND	
Ethernet	<ul style="list-style-type: none">• 1 x RJ-45 Female, 10/100Base-T• Supported Protocol: ARP, ICMP, TCP/IP, DHCP, HTTPS, SSH• DHCP-enabled. The following default IP settings will be used if no IP is assigned within 30 seconds: IP: 192.168.0.60 Subnet Mask: 255.255.255.0		
Switches			
Controller ID	1 x 16-segment Switch		
Expander ID	1 x 8-segment Switch		
Reset Button	1 x Semi-recessed Pushbutton		
USB	1 x USB Type A		
Power Consumption	DC5V:3.8W:28BTU/h DC48V:4.75W:33BTU/h Note: <ul style="list-style-type: none">● The measurement in Watts indicates the typical power consumption of the device with no external loading.● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.		
Environmental			
Operating Temperature	0 – 50°C		
Storage Temperature	–20 – 60°C		
Humidity	0 - 80% RH, Non-Condensing		
Physical Properties			
Housing	Metal		
Weight	0.45 kg (0.99 lb)		
Dimensions (L x W x H)	13.00 x 7.58 x 4.20 cm (5.12 x 2.98 x 1.65 in.)		
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.		

Diagram


ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.