

VS0201

2-Port VGA/Audio Switch




The VS0201 2-Port VGA Switch with Audio allows you to connect two audio/video source computers to a single monitor or projector with full audio and quickly switch between the devices for use.

VS0201 built-in bi-directional RS-232 serial port for high-end system control, and advanced RS-232 control. With the ability to use high-end serial control devices via RS-232 commands allows the VS0201 to be controlled by secondary systems with advanced functions such as; port switching, auto switching, front panel pushbutton lock, and Power on Detection.

The VS0201 is perfect for the [meeting room](#), media centers, class rooms, or any [presentation](#) environment requiring multiple audio/video sources to be accessed on a single display.

**RS-232
Control**

VDS Video
DynaSync



Video In

HDB-15



Video Out

HDB-15



**Stereo
Audio**

Features

- Displays the video output of two computers on a single monitor or projector
- Quick and easy switching between VGA/Audio sources via front panel pushbuttons, RS-232, or IR remote control
- Superior video quality – up to 1920 x 1440
- Long-distance transmission – up to 30 m *
- Supports VGA, SVGA, UXGA, WUXGA and multisync monitors
- [Video DynaSync™ – Exclusive ATEN technology eliminates boot-up display problems and optimizes resolution when switching between ports](#)
- Built-in bi-directional RS-232 serial port for high-end system control **
- RS-232 Control:
 - Power On Detection – if one VGA source is powered off, the VS0201 will automatically switch to the next powered-on source
 - [Auto Switching](#) – sets the priority for auto switching to a connected port
 - [Pushbutton Lock](#) – locks use of the front panel pushbuttons
- Supports stereo audio
- DDC compatible
- Supports up to 300MHz bandwidth for optimal video quality
- LED indication of power status and source device
- All-metal casing provides durability and protection
- Plug-and-play – no software installation required

* Video content sent over very long distance using a VGA cable might result in slight degradation of the video signal and quality.


** Note: The VS0201 AP and GUI operation instructions can be downloaded from the ATEN website (www.aten.com)

Specifications

Video Input	
Interfaces	2 x HDB-15 Male (Blue)
Impedance	75 Ω
Max. Distance	1.8 m
Video Output	
Interfaces	1 x HDB-15 Female (Blue)
Impedance	75 Ω
Max. Distance	30 m
Video	
Max. Bandwidth	300 MHz
Max. Resolution	Up to 1920 x 1440
Max. Distance	Up to 30 m
Audio	
Input	2 x Mini Stereo Jack Female (Green)
Output	1 x Mini Stereo Jack Female (Green)
Control	
RS-232	Connector: 1 x DB-9 Female (Black) Baud Rate and Protocol: Baud Rate: 19200, Data Bits: 8, Stop Bits:1, Parity: No, Flow Control: No
IR	1 x Mini Stereo Jack Female (Black)
Connectors	

Power	1 x DC Jack
Power Consumption	DC5.3V:0.55W:3BTU/h Note: <ul style="list-style-type: none"> ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.
Environmental	
Operating Temperature	0 - 50°C
Storage Temperature	-20 - 60°C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Metal
Weight	0.45 kg (0.99 lb)
Dimensions (L x W x H)	13.00 x 7.61 x 4.40 cm (5.12 x 3 x 1.73 in.)
Carton Lot	5 pcs
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their
 respective owners.