

VS291

2-Port VGA Switch



The VS291 is a video switch with 2 ports. It allows 2 independent computers to display their video outputs on a single monitor. Therefore, users will not need to buy monitors for each computer additionally.



Features

- Displays the video output of two computers on a single monitor or projector.
- Computer selection via pushbutton switch.
- Electronic switching for greater reliability and durability.
- Easy Installation - No Software Required.
- Long distance transmission - up to 10m
- High resolution video - up to 1920 x 1440.
- DDC, DDC2, DDC2B Compatible.
- Supports VGA, XGA, SVGA, UXGA and Multisync monitors.
- OS Support: Windows 2000, Windows XP, Linux, Mac and Sun

Specifications

2-Port Video Switch

Video Input	
Interfaces	2 x HDB-15 Female (Blue)
Impedance	75 Ω
Max. Distance	1.8 m
Video Output	
Interfaces	1 x HDB-15 Female (Blue)
Impedance	75 Ω
Max. Distance	10 m
Video	
Max. Bandwidth	150 MHz
Max. Resolution	Up to 1920 x 1440
Max. Distance	Up to 10 m
Power	Connector: 1 x DC Jack Consumption: 9 VDC, 0.9W
Environmental	
Operating Temperature	0 - 50°C
Storage Temperature	-20 - 60°C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Plastic / Metal
Weight	0.15 kg (0.33 lb)
Dimensions (L x W x H)	12.00 x 6.52 x 4.40 cm (4.72 x 2.57 x 1.73 in.)
Carton Lot	20 pcs
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.